


VEGA S W Duo

LW7037.519-EN-M-M-700-740











Medium (Up & Down)

Configuration

Light distribution [M-M] 60° **Delivered lumens flux** 1463 lm Rated input power 18 W **Color temperature** 4000 K CRI 70 **Luminaire efficacy** 73 lm/W Lamp 2 LED **Color Deviation** 5 SDCM **BUG** rating B1-U0-G0 Lifetime L90 (hour) >72,600 Lifetime L80 (hour) >72,600

Options

Tochnical information

Technical inform	ation
Mounting	Wall mountable
Housing	Corrosion resistant, marine grade aluminum
	housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	High reflectance aluminium coating [S] [N],
	PMMA lens with high optical efficiency [MN] [M]
Glass / Diffusor	Tempered safety glass
Impact protection	IK07
Ingress protection	IP65
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	2.56 kg
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	2/2 kV
protection	
Power factor	> 0.90
Through wiring	Single power cord entry
Operating	-4050°C
temperature	

8" of flexible power cord Power cord Notes Please consult factory for combinations of different beam spreads.

Accessories (To be ordered separately)

Optical accessories



Visor for VEGA S

100708016

Project na	me		Туре	Quantity	
Date		Note			

LW7037.519-EN-M-M-700-740-__--_

Light distribution	Rated input power	Color temperature	Control	Product colors			
[M-M] Medium (Up & Down) - 60°	[700] 18 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black			
[S-S] Spot - NEMA Type 0 (Up & Down) - 7°		[827] 2700 K CRI 80	[DALI] DALI	[HM2] Dark gray			
		3000 K CRI 80		[HM3] Anthracite gray			
[N-N] Narrow - NEMA Type 2 (Up & Down) - 26°		[840] 4000 K CRI 80		[HM4] Light gray			
[MN-MN] Medium Narrow (Up & Down) - 42°				[HM5] White			
				[HM6] Bronze			
				[CC] Custom color (Plea specify RAL code)			
Extras	Accessories (To be ordered separately)			I			
Consult the factory	Optical accessories						
[UNI] 120-277V 50/60Hz	[100708016] Visor for VEGA S						
Luminaire body options	1						
[DPC] Double powder coating							