

### **VEGA S W Duo**

# heper to hep

#### LW7037.519-EN-S-S-700-830





**86 mm** 3 25/64"



**[S-S]** Spot - NEMA Type 0 (Up & Down)

### Configuration

**Light distribution** [S-S] 7° **Delivered lumens flux** 1888 lm Rated input power 18 W **Color temperature** 3000 K CRI 80 **Luminaire efficacy** 104 lm/W Lamp 2 LED **Color Deviation** 5 SDCM **BUG** rating B1-U0-G0 Lifetime L90 (hour) >72,600 Lifetime L80 (hour) >72,600

#### Options

#### Technical information

recinical informa	ation
Mounting	Wall mountable
Housing	Corrosion resistant, marine grade aluminum
	housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	High reflectance aluminium coating [S] [N],
	PMMA lens with high optical efficiency [MN] [M]
Glass / Diffusor	Tempered safety glass
Impact protection	IK07
Ingress protection	IP65
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	2.56 kg
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	2/2 kV
protection	
Power factor	> 0.90
Through wiring	Single power cord entry
Operating	-4050°C
temperature	

Power cord8" of flexible power cordNotesPlease consult factory for combinations of<br/>different beam spreads.

We reserve the right to change specifications without prior

written notice. Edition: 18.05.2024. For current version visit

heperlighting.com. All flux (±%7 tolerance) and power values

(±%10 tolerance) are derived following appropriate IES, CIE,

and applicable standards.

## Accessories (To be ordered separately)

Optical accessories



Visor for VEGA S

100708016

Project na	me		Туре	Quantity	
Date		Note			

## LW7037.519-EN-S-S-700-830-\_\_--\_\_-

Light distribution	Rated input power	Color temperature	Control	Product colors
[S-S] Spot - NEMA Type 0	[ <b>700]</b> 18 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[HM1] Black
(Úp & Down) - 7°  [N-N]  Narrow - NEMA Type		[ <b>827</b> ] 2700 K CRI 80	[DALI] DALI	[HM2] Dark gray
2 (Up & Down) - 26°		<b>[740]</b> 4000 K CRI 70		[HM3] Anthracite gray
[MN-MN] Medium Narrow (Up & Down) - 42°		[ <b>840]</b> 4000 K CRI 80		[HM4] Light gray
[M-M] Medium (Up & Down) - 60°				[HM5] White
				[HM6] Bronze
				Custom color (Please specify RAL code)
Extras	Accessories (To be ordered separately)			
Consult the factory	Optical accessories			
<b>[UNI]</b> 120-277V 50/60Hz	[100708016] Visor for VEGA S			
Luminaire body options				
[DPC] Double powder coating				