


### **VEGA S W Duo**

#### LW7037.519-US-MN-MN-700-840











[MN-MN] Medium Narrow (Up & Down)

### Configuration

**Light distribution** [MN-MN] 42° **Delivered lumens flux** 1534 lm Rated input power 18 W **Color temperature** 4000 K CRI 80 **Luminaire efficacy** 76 lm/W Lamp 2 LED **Color Deviation** 5 SDCM **BUG** rating B1-U0-G0 Lifetime L90 (hour) >72,600 Lifetime L80 (hour) >72,600

#### Options

#### Tochnical information

Technical inform	ation
Mounting	Wall mountable
Housing	Corrosion resistant, marine grade aluminum
	housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	High reflectance aluminium coating [S] [N],
	PMMA lens with high optical efficiency [MN] [M]
Glass / Diffusor	Tempered safety glass
Impact protection	IK07
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	5.6 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	2/2 kV
protection	
Power factor	> 0.90
Through wiring	Single power cord entry
Operating	-4050°C
temperature	

8" of flexible power cord **Power cord** Notes Please consult factory for combinations of

We reserve the right to change specifications without prior

written notice. Edition: 13.05.2024. For current version visit

heperlighting.com. All flux (±%7 tolerance) and power values

(±%10 tolerance) are derived following appropriate IES, CIE,

and applicable standards.

different beam spreads.

# Accessories (To be ordered separately)

Optical accessories



Visor for VEGA S

100708016

Project na	me		Туре	Quantity	
Date		Note			

## LW7037.519-US-MN-MN-700-840-\_\_--\_

Light distribution	Rated input power	Color temperature	Control	Product colors
[MN-MN] Medium Narrow (Up & Down) - 42°	[ <b>700]</b> 18 W	[ <b>840</b> ] 4000 K CRI 80	[ONOFF] On/Off	[HM1] Black
[S-S] Spot - NEMA Type 0		[ <b>827]</b> 2700 K CRI 80	[ <b>0-10V</b> ] 0-10V	[HM2] Dark gray
(Úp & Down) - 7°		[ <b>830]</b> 3000 K CRI 80		[HM3] Anthracite gray
[ <b>N-N]</b> Narrow - NEMA Type 2 (Up & Down) - 26°		[ <b>740]</b> 4000 K CRI 70		[HM4] Light gray
[M-M] Medium (Up & Down) - 60°				[HM5] White
				[HM6] Bronze
				Custom color (Pleas specify RAL code)
Extras	Accessories (To be ordered separately)			
Luminaire body	Optical accessories			
<b>[DPC]</b> Double powder coating	- <b>[100708016]</b> Visor for VEGA S			