


VEGA S W Duo

LW7037.519-US-MN-MN-700-827











[MN-MN] Medium Narrow (Up & Down)

Configuration

Light distribution [MN-MN] 42° **Delivered lumens flux** 1350 lm Rated input power 18 W **Color temperature** 2700 K CRI 80 **Luminaire efficacy** 67 lm/W Lamp 2 LED **Color Deviation** 5 SDCM **BUG** rating B1-U0-G0 Lifetime L90 (hour) >72,600 Lifetime L80 (hour) >72,600

Options

ation
Wall mountable
Corrosion resistant, marine grade aluminum
housing
Chromate conversion pretreatment followed by
electrostatic powder coating
Stainless steel (AISI 304 / EN 1.4301 grade)
Liquid silicone
High reflectance aluminium coating [S] [N],
PMMA lens with high optical efficiency [MN] [M]
Tempered safety glass
IK07
IP65
120-277V 50/60Hz
Class I
5.6 lbs
Multi-chip high power LEDs on metal-core PCB
Internal LED driver
2/2 kV
> 0.90
Single power cord entry
-4050°C

8" of flexible power cord **Power cord** Notes Please consult factory for combinations of

different beam spreads.

and applicable standards.

Accessories (To be ordered separately)

Optical accessories



Visor for VEGA S

100708016

Project na	me		Туре	Quantity	
Date		Note			

LW7037.519-US-MN-MN-700-827-__--_

Light distribution	Rated input power	Color temperature	Control	Product colors
[MN-MN] Medium Narrow (Up & Down) - 42°	[700] 18 W	[827] 2700 K CRI 80	[ONOFF] On/Off	[HM1] Black
[S-S] Spot - NEMA Type 0		[830] 3000 K CRI 80	[0-10V] 0-10V	[HM2] Dark gray
(Úp & Down) - 7°		[740] 4000 K CRI 70		[HM3] Anthracite gray
[N-N] Narrow - NEMA Type 2 (Up & Down) - 26°		[840] 4000 K CRI 80		[HM4] Light gray
[M-M] Medium (Up & Down) - 60°				[HM5] White
				[HM6] Bronze
				Custom color (Pleas specify RAL code)
Extras	Accessories (To be ordered separately)			
Luminaire body	Optical accessories			
[DPC] Double powder coating	- [100708016] Visor for VEGA S			