
VEGA S W Duo


IK07 IP65






LW7037.519-US-S-S-700-830-UNI-C1











[S-S] Spot (Up & Down)

Variant

Light distribution [S-S] 7° **Delivered lumens flux** 1888 lm Rated input power 18 W **Colour temperature** 3000 K CRI 80 **Luminaire efficacy** 104 lm/W Lamp 2 LED MacAdam Ellipse 5 SDCM B1-U0-G0 **BUG** rating Lifetime L90B50 (hour) >72,600 Lifetime L80B50 (hour) >72,600

Options

Technical information

rechnical informa	ation
Mounting	Wall mountable
Housing	Corrosion resistant, marine grade aluminum
	housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	High reflectance aluminium coating [S] [N],
	PMMA lens with high optical efficiency [MN] [M]
Glass / Diffusor	Tempered safety glass
Impact protection	IK07
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	5.6 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	2/2 kV
protection	
Power factor	> 0.90
Through wiring	Single cable entry
Operating	-4050°C
temperature	

0.2 m of flexible cable Cable Notes Please consult factory for combinations of different light distributions.

Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 18.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Accessories (To be ordered separately)

Optical accessories



Visor for VEGA S

100708016

Project na	me		Туре	Quantity	
Date		Note			

LW7037.519-US-S-S-700-830-__-UNI-C1-__--

Light distribution	Rated input power	Colour temperature	Control	Product colours
[S-S] Spot (Up & Down) - 7°	[700] 18 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[HM1] Black
[N-N] Narrow (Up & Down) - 26° [MN-MN] Medium Narrow (Up & Down) - 42° [M-M] Medium (Up & Down) - 60°		[827] 2700 K CRI 80	[0-10V] 0-10V	[HM2] Dark grey
		[740] 4000 K CRI 70		[HM3] Anthracite grey
		[840] 4000 K CRI 80		[HM4] Light grey
				[HM5] White
				[HM6] Bronze
				[CC] Custom colour (Pleas specify RAL code)
Extras	Accessories (To be ordered separately)			
Luminaire body	Optical accessories			
[DPC] Double powder coating	[100708016] Visor for VEGA S			