



TURA 2x12 LED



IK08 IP66



LL2036.752-EN-T3-2-700-730-EN-C1



[T3]

Type III, Asymmetric,
Side throw

Variant

Light distribution	[T3] 158x59°
Delivered lumens flux	6391 lm
Rated input power	52 W
Colour temperature	3000 K CRI 70
Luminaire efficacy	122 lm/W
Lamp	24 LED
MacAdam Ellipse	3 SDCM
BUG rating	B3-U1-G3
Lifetime L90B50 (hour)	>102,000
Lifetime L80B50 (hour)	>102,000

Options

Technical information

Mounting	Direct pole or side bracket mountable. Spigot: Ø60 mm x 100 mm
Tilt angle	+15°/-15°
Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	EPDM gasket (Shore A 20-25)
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP66
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Wind catching area (EPA)	0.25 m ²
Weight	10 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	8/6 kV
Power factor	> 0.95
Through wiring	Single cable entry
Operating temperature	-40...50°C
Notes	This product can be supplied with Insulation class (Class II) upon request. Please contact factory.

HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,
Sincan, 06909 Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 237 2901 2975
infoEU@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 21.05.2024.
For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Poles (To be ordered separately)

Conical aluminum poles with flange plate

	Product code	Height	Diameter / Dimensions	Spigot diameter
	PAFK.D114	3m, 4m, 5m m	Ø114mm	Ø60mm, Ø76mm mm
	PAFK.D122	4m, 5m, 6m m	Ø122mm	Ø60mm, Ø76mm mm
	PAFK.D148	6m, 7m, 8m m	Ø148mm	Ø60mm, Ø76mm mm
	PAFK.D165	6m, 7m, 8m, 9m m	Ø165mm	Ø76mm, Ø90mm mm
	PAFK.D180	10m, 8m, 9m m	Ø180mm	Ø76mm, Ø90mm mm
	PAFK.D200	10m, 11m, 12m m	Ø200mm	Ø76mm, Ø90mm mm

Conical aluminum poles with embedded base

	Product code	Height	Diameter / Dimensions	Spigot diameter
	PABK.D114	3m, 4m, 5m m	Ø114mm	Ø60mm, Ø76mm mm
	PABK.D122	4m, 5m, 6m, 7m m	Ø122mm	Ø60mm, Ø76mm mm
	PABK.D148	6m, 7m, 8m m	Ø148mm	Ø60mm, Ø76mm mm
	PABK.D165	6m, 7m, 8m, 9m m	Ø165mm	Ø76mm, Ø90mm mm
	PABK.D180	10m, 8m, 9m m	Ø180mm	Ø76mm, Ø90mm mm
	PABK.D200	10m, 11m, 12m m	Ø200mm	Ø76mm, Ø90mm mm

Cylindrical aluminum poles with flange plate

	Product code	Height	Diameter / Dimensions	Spigot diameter
	PAFC.D114	3m, 4m, 5m m	Ø114mm	Ø114mm mm
	PAFC.D122	3m, 4m, 5m, 6m m	Ø122mm	Ø122mm mm
	PAFC.D148	6m, 7m, 8m m	Ø148mm	Ø148mm mm
	PAFC.D165	6m, 7m, 8m, 9m m	Ø165mm	Ø165mm mm

Project name		Type		Quantity	
Date		Note			
LL2036.752-EN-T3-2-700-730-__-EN-C1-__-__-__-__-__-__					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[T3] Type III, Asymmetric, Side throw - 158x59°	[700] 52 W	[730] 3000 K CRI 70	[ONOFF] On/Off	[HM3]  Anthracite grey
[P4] Special pedestrian road distribution-right side traffic - 22x77°		[830] 3000 K CRI 80	[DALI] DALI	[HM4]  Light grey
[T1] Type I, Asymmetric, Side throw - 113x48°		[740] 4000 K CRI 70	[AUTO] AutoDIM	[CC]  Custom colour (Please specify RAL code)
[T2] Type II, Asymmetric, Side throw - 137x52°			[STEP] StepDIM	
[T2] Type II, Asymmetric, Side throw - 150x60°				
[T2BL] Type II, Asymmetric, Side throw with Backlight shield - 128x48°				
[T3] Type III, Asymmetric, Side throw - 143x68°				
[T3BL] Type III, Asymmetric, Side throw with Backlight shield - 128x50°				
[T4] Type IV, Asymmetric, Forward throw - 121x70°				
[T4BL] Type IV, Asymmetric, Forward throw with Backlight shield - 111x38°				
Extras				

External surge protection
[SP10] 10 kV
Connectivity
[NM7] NEMA socket - 7 Pin
Light output
[CLO] Constant light output
Consult the factory
[C2] Class II
[UNI] 120-277V 50/60Hz
Luminaire body options
[DPC] Double powder coating