



# TURA 3x12 LED



IK08 IP66



LL2036.753-EN-T3-2-700-730-EN-C1



[T3]

Type III, Asymmetric,  
Side throw

## Variant

|                        |               |
|------------------------|---------------|
| Light distribution     | [T3] 158x59°  |
| Delivered lumens flux  | 9587 lm       |
| Rated input power      | 80 W          |
| Colour temperature     | 3000 K CRI 70 |
| Luminaire efficacy     | 119 lm/W      |
| Lamp                   | 36 LED        |
| MacAdam Ellipse        | 3 SDCM        |
| BUG rating             | B3-U1-G3      |
| Lifetime L90B50 (hour) | >102,000      |
| Lifetime L80B50 (hour) | >102,000      |

## Options

## Technical information

|                          |                                                                                                     |
|--------------------------|-----------------------------------------------------------------------------------------------------|
| Mounting                 | Direct pole or side bracket mountable. Spigot: Ø60 mm x 100 mm                                      |
| Tilt angle               | +15°/-15°                                                                                           |
| Housing                  | Corrosion resistant, die-cast, marine grade aluminum housing                                        |
| Finishing                | Chromate conversion pretreatment followed by electrostatic powder coating                           |
| Fasteners                | Stainless steel (AISI 304 / EN 1.4301 grade)                                                        |
| Gasket                   | EPDM gasket (Shore A 20-25)                                                                         |
| Lens / Reflector         | PMMA lens with high optical efficiency                                                              |
| Glass / Diffusor         | Tempered safety glass                                                                               |
| Impact protection        | IK08                                                                                                |
| Ingress protection       | IP66                                                                                                |
| Input voltage            | 220-240V 50/60Hz                                                                                    |
| Insulation class         | Class I                                                                                             |
| Wind catching area (EPA) | 0.25 m <sup>2</sup>                                                                                 |
| Weight                   | 10 kg                                                                                               |
| LED module               | High power LEDs on metal-core PCB                                                                   |
| Driver                   | Internal LED driver                                                                                 |
| Driver surge protection  | 8/6 kV                                                                                              |
| Power factor             | > 0.95                                                                                              |
| Through wiring           | Single cable entry                                                                                  |
| Operating temperature    | -40...50°C                                                                                          |
| Notes                    | This product can be supplied with Insulation class (Class II) upon request. Please contact factory. |

HPR Pazarlama A.Ş.  
Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,  
Sincan, 06909 Ankara, Turkey  
+90 312 267 54 30  
info@hepergroup.com

HEPER Europe GmbH  
Ahornweg 5a, 58675  
Hemer, Germany  
+49 237 2901 2975  
infoEU@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 18.05.2024.  
For current version visit [heperlighting.com](http://heperlighting.com). All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

## Poles (To be ordered separately)

### Conical aluminum poles with flange plate



| Product code | Height           | Diameter / Dimensions | Spigot diameter |
|--------------|------------------|-----------------------|-----------------|
| PAFK.D114    | 3m, 4m, 5m m     | Ø114mm                | Ø60mm, Ø76mm mm |
| PAFK.D122    | 4m, 5m, 6m m     | Ø122mm                | Ø60mm, Ø76mm mm |
| PAFK.D148    | 6m, 7m, 8m m     | Ø148mm                | Ø60mm, Ø76mm mm |
| PAFK.D165    | 6m, 7m, 8m, 9m m | Ø165mm                | Ø76mm, Ø90mm mm |
| PAFK.D180    | 10m, 8m, 9m m    | Ø180mm                | Ø76mm, Ø90mm mm |
| PAFK.D200    | 10m, 11m, 12m m  | Ø200mm                | Ø76mm, Ø90mm mm |

### Conical aluminum poles with embedded base



| Product code | Height           | Diameter / Dimensions | Spigot diameter |
|--------------|------------------|-----------------------|-----------------|
| PABK.D114    | 3m, 4m, 5m m     | Ø114mm                | Ø60mm, Ø76mm mm |
| PABK.D122    | 4m, 5m, 6m, 7m m | Ø122mm                | Ø60mm, Ø76mm mm |
| PABK.D148    | 6m, 7m, 8m m     | Ø148mm                | Ø60mm, Ø76mm mm |
| PABK.D165    | 6m, 7m, 8m, 9m m | Ø165mm                | Ø76mm, Ø90mm mm |
| PABK.D180    | 10m, 8m, 9m m    | Ø180mm                | Ø76mm, Ø90mm mm |
| PABK.D200    | 10m, 11m, 12m m  | Ø200mm                | Ø76mm, Ø90mm mm |

### Cylindrical aluminum poles with flange plate



| Product code | Height           | Diameter / Dimensions | Spigot diameter |
|--------------|------------------|-----------------------|-----------------|
| PAFC.D114    | 3m, 4m, 5m m     | Ø114mm                | Ø114mm mm       |
| PAFC.D122    | 3m, 4m, 5m, 6m m | Ø122mm                | Ø122mm mm       |
| PAFC.D148    | 6m, 7m, 8m m     | Ø148mm                | Ø148mm mm       |
| PAFC.D165    | 6m, 7m, 8m, 9m m | Ø165mm                | Ø165mm mm       |

|                                                           |  |             |  |                 |  |
|-----------------------------------------------------------|--|-------------|--|-----------------|--|
| <b>Project name</b>                                       |  | <b>Type</b> |  | <b>Quantity</b> |  |
| <b>Date</b>                                               |  | <b>Note</b> |  |                 |  |
| <b>LL2036.753-EN-T3-2-700-730-__-EN-C1-__-__-__-__-__</b> |  |             |  |                 |  |

| Light distribution                                                                           | Rated input power    | Colour temperature            | Control                  | Product colours                                                                                                                               |
|----------------------------------------------------------------------------------------------|----------------------|-------------------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <b>[T3]</b><br>Type III, Asymmetric,<br>Side throw - 158x59°                                 | <b>[700]</b><br>80 W | <b>[730]</b><br>3000 K CRI 70 | <b>[ONOFF]</b><br>On/Off | <b>[HM3]</b> <br>Anthracite grey                           |
| <b>[P4]</b><br>Special pedestrian<br>road distribution-right<br>side traffic - 22x77°        |                      | <b>[830]</b><br>3000 K CRI 80 | <b>[DALI]</b><br>DALI    | <b>[HM4]</b> <br>Light grey                                |
| <b>[T1]</b><br>Type I, Asymmetric,<br>Side throw - 113x48°                                   |                      | <b>[740]</b><br>4000 K CRI 70 | <b>[AUTO]</b><br>AutoDIM | <b>[CC]</b> <br>Custom colour (Please<br>specify RAL code) |
| <b>[T2]</b><br>Type II, Asymmetric,<br>Side throw - 137x52°                                  |                      |                               | <b>[STEP]</b><br>StepDIM |                                                                                                                                               |
| <b>[T2]</b><br>Type II, Asymmetric,<br>Side throw - 150x60°                                  |                      |                               |                          |                                                                                                                                               |
| <b>[T2BL]</b><br>Type II, Asymmetric,<br>Side throw with<br>Backlight shield -<br>128x48°    |                      |                               |                          |                                                                                                                                               |
| <b>[T3]</b><br>Type III, Asymmetric,<br>Side throw - 143x68°                                 |                      |                               |                          |                                                                                                                                               |
| <b>[T3BL]</b><br>Type III, Asymmetric,<br>Side throw with<br>Backlight shield -<br>128x50°   |                      |                               |                          |                                                                                                                                               |
| <b>[T4]</b><br>Type IV, Asymmetric,<br>Forward throw -<br>121x70°                            |                      |                               |                          |                                                                                                                                               |
| <b>[T4BL]</b><br>Type IV, Asymmetric,<br>Forward throw with<br>Backlight shield -<br>127x32° |                      |                               |                          |                                                                                                                                               |
| <b>Extras</b>                                                                                |                      |                               |                          |                                                                                                                                               |

|                                       |
|---------------------------------------|
| <b>Connectivity</b>                   |
| <b>[NM7]</b><br>NEMA socket - 7 Pin   |
| <b>Light output</b>                   |
| <b>[CLO]</b><br>Constant light output |
| <b>Consult the factory</b>            |
| <b>[C2]</b><br>Class II               |
| <b>[UNI]</b><br>120-277V 50/60Hz      |
| <b>Luminaire body options</b>         |
| <b>[DPC]</b><br>Double powder coating |