


LR9012.584-EN-WW-350-840-EN-C1-SS











Wall-wash

Variant

СЕ ЦКА ІКОВ ІР67 →

Light distribution	[WW] 45x85°
Delivered lumens flux	2649 lm
Rated input power	30 W
Colour temperature	4000 K CRI 80
Luminaire efficacy	88 lm/W
Lamp	12 LED
MacAdam Ellipse	3 SDCM
Lifetime L90B50 (hour)	>42,000
Lifetime L80B50 (hour)	>42,000

Options

Cable

Technical information

Mounting	Ground recessed mountable
Housing	Corrosion resistant stainless steel housing (AISI
	316L / EN 1.4571 grade)
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating,
	multifaceted micro reflector
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP67
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	7.88 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	4/4 kV
protection	
Power factor	> 0.97
Through wiring	Single cable entry
Operating	-4050°C
temperature	
-	

0.3 m of rubber-sheated cable

HPR Pazarlama A.Ş.

Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com

HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 17.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

1/3



Accessories (Included)

Accessories (To be ordered separately)

Mounting accessories



Aluminium case for ZETA 12 Dyno / MOLTO 6 Hybrid

007500402

Mounting accessories Mounting

Mounting accessories Mounting accessories





Case removing Connector set - 5pole 160404012 141407400 0000

Junction Box 141901135

HPR Pazarlama A.Ş. Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com

HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 17.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

2/3

Project na	me				Туре	Quantity	
Date			Note				
LR9012.	584-EN-W	/W-350-8	40EN	-C1-SS			

[840] 4000 K CRI 80 [827] 2700 K CRI 80 [830] 3000 K CRI 80 [740] 4000 K CRI 70	[ONOFF] On/Off [DALI] DALI	[SS] Stainless steel
2700 K CRI 80 [830] 3000 K CRI 80 [740]		
3000 K CRI 80 [740]		
e		
ŀ	le	le

HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 17.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.