

ZETA 4 Dyno


CE UK IKO8 IP67



LR9012.582-EN-WW-350-827-EN-C1-SS









Variant

Light distribution [WW] 49x33° Delivered lumens flux 793 lm Rated input power 10 W **Colour temperature** 2700 K CRI 80 79 lm/W **Luminaire efficacy** Lamp 4 LED MacAdam Ellipse 3 SDCM Lifetime L90B50 (hour) >42,000 Lifetime L80B50 (hour) >42,000

Options

temperature

Technical information

Mounting Ground recessed mountable Corrosion resistant stainless steel housing (AISI Housing 316L / EN 1.4571 grade) **Fasteners** Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Silicone Lens / Reflector High reflectance aluminium coating, multifaceted micro reflector Glass / Diffusor Tempered safety glass IK08 Impact protection IP67 Ingress protection Input voltage 220-240V 50/60Hz **Insulation class** Class I Weight 2.77 kg High power LEDs on metal-core PCB **LED** module Internal LED driver Driver 1/1 kV **Driver surge** protection **Power factor** > 0.90 Through wiring Single cable entry Operating -30...50°C

Cable 0.3 m of rubber-sheated cable

Mounting accessories



Aluminium case for ZETA 4 Dyno / MOLTO 2 Hybrid

007500582

Mounting accessories



Case removing vacuum

160404012

Mounting accessories Mounting accessories



Connector set - 5pole

141407400



Junction Box

141901135

Project na	me		Туре	Quantity	
Date		Note			

LR9012.582-EN-WW-350-827-__--EN-C1-SS

[250]			[SS] Stainless steel	
[350] 10 W	[827] 2700 K CRI 80	[ONOFF] On/Off		
	[830] 3000 K CRI 80	[DALI] DALI		
	[740] 4000 K CRI 70			
	[840] 4000 K CRI 80			
Accessories (To be ordered separately)				
Mounting accessories				
[160404012] Case removing vacuum				
[141407400] Connector set - 5-pole				
[141901135] Junction Box				
	ordered separately) Mounting accessories [160404012] Case removing vacuum [141407400] Connector set - 5-pole [141901135]	3000 K CRI 80 [740] 4000 K CRI 70 [840] 4000 K CRI 80 4000 K CRI 70 4000 K CRI 80 4000 K CRI 8	3000 K CRI 80 DALI	