

ZETA 4 Dyno


CE UK IKO8 IP67



LR9012.582-EN-WW-350-840-EN-C1-SS









Variant

Light distribution [WW] 49x33° Delivered lumens flux 880 lm Rated input power 10 W **Colour temperature** 4000 K CRI 80 88 lm/W **Luminaire efficacy** Lamp 4 LED MacAdam Ellipse 3 SDCM Lifetime L90B50 (hour) >42,000 Lifetime L80B50 (hour) >42,000

Options

temperature

Technical information

Mounting Ground recessed mountable Corrosion resistant stainless steel housing (AISI Housing 316L / EN 1.4571 grade) **Fasteners** Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Silicone Lens / Reflector High reflectance aluminium coating, multifaceted micro reflector Glass / Diffusor Tempered safety glass IK08 Impact protection IP67 Ingress protection Input voltage 220-240V 50/60Hz **Insulation class** Class I Weight 2.77 kg High power LEDs on metal-core PCB **LED** module Internal LED driver Driver 1/1 kV **Driver surge** protection **Power factor** > 0.90 Through wiring Single cable entry Operating -30...50°C

Cable 0.3 m of rubber-sheated cable


Mounting accessories



Aluminium case for ZETA 4 Dyno / MOLTO 2 Hybrid

007500582

Mounting accessories



Mounting accessories Mounting accessories



Case removing vacuum

160404012



Connector set - 5pole

141407400



Junction Box

141901135

Project name					Туре	Quantity	
Date			Note				

LR9012.582-EN-WW-350-840-___-EN-C1-SS

Light distribution	Rated input power	Colour temperature	Control	Product colours	
[WW] Wall-wash - 49x33°	[350] 10 W	[840] 4000 K CRI 80	[ONOFF] On/Off	[SS] Stainless steel	
		[827] 2700 K CRI 80	[DALI] DALI		
		[830] 3000 K CRI 80			
		[740] 4000 K CRI 70			
Accessories (Included)	Accessories (To be ordered separately)				
Mounting accessories	Mounting accessories				
[007500582] Aluminium case for ZETA 4 Dyno / MOLTO	[160404012] Case removing vacuum				
2 Hybrid	[141407400] Connector set - 5-pole				
	[141901135] Junction Box				