


MOLTO 4 Hybrid

heper, t

LR9012.695-EN-N-700-840-SS









Narrow - NEMA Type

Configuration

Light distribution [N] 26° **Delivered lumens flux** 3810 lm 35 W Rated input power **Color temperature** 4000 K CRI 80 95 lm/W **Luminaire efficacy** 4 LED Lamp **Color Deviation** 5 SDCM Lifetime L90 (hour) >72,600 Lifetime L80 (hour) >72,600

Options

temperature Power cord

Technical information

Mounting	Ground recessed mountable
Housing	Corrosion resistant stainless steel housing (AISI
	316L / EN 1.4571 grade)
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP67
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	5.37 kg
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	External LED driver
Driver surge	4/4 kV
protection	
Power factor	> 0.97
Through wiring	Single power cord entry
Operating	-4050°C

12" of rubber-sheated power cord

Mounting accessories



Aluminium case for ZETA 8 Dyno / MOLTO 4 Hybrid

007500618

Mounting accessories Mounting accessories Mounting accessories

Case removing

vacuum

160404012





Connector set - 5pole

141407400



Junction Box

141901135

Project na	me		Туре	Quantity	
Date		Note			

LR9012.695-EN-N-700-840-___-SS-__

Light distribution	Rated input power	Color temperature	Control	Product colors
[N] Narrow - NEMA Type	[700] 35 W	[840] 4000 K CRI 80	[ONOFF] On/Off	[SS] Stainless steel
2 - 26° [S] Spot - NEMA Type 0 - 7°		[827] 2700 K CRI 80	[DALI] DALI	
		[830] 3000 K CRI 80		
		[740] 4000 K CRI 70		
Extras	Accessories (Included)	Accessories (To be ordered separately)		
Consult the factory	Mounting	Mounting		
[UNI]	accessories	accessories		
120-277V 50/60Hz	[007500618] Aluminium case for ZETA 8 Dyno / MOLTO 4 Hybrid	[160404012] Case removing vacuum		
		[141407400] Connector set - 5-pole		
		[141901135] Junction Box		