


## LD8017.693-US-N-700-740



☐ **246 mm** 9 11/16" ☐ \_

**Ø86 mm** 3 25/64"





## Configuration

Light distribution	[N] 26°
Delivered lumens flux	1019 lm
Rated input power	10 W
Color temperature	4000 K CRI 70
Luminaire efficacy	101 lm/W
Lamp	1 LED
Color Deviation	5 SDCM
BUG rating	B1-U0-G0
Lifetime L90 (hour)	>72,600
Lifetime L80 (hour)	>72,600

#### Options

### Technical information

Mounting	Ceiling mountable
Housing	Corrosion resistant, die-cast, marine grade
	aluminum housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone rubber
Lens / Reflector	High reflectance aluminium coating [S] [N],
	PMMA lens with high optical efficiency [MN] [M]
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	2.5 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	1/1 kV
protection	
Power factor	> 0.90
Through wiring	Single power cord entry
Operating	-4050°C
temperature	
Power cord	8" of flexible power cord

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com

# Accessories (To be ordered separately)

Optical accessories



Visor for PUNTO S

007502282

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 04.05.2024. For current version visit heperlighting.com. All flux ( $\pm$ %7 tolerance) and power values ( $\pm$ %10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project na	me			Туре	Quantity		
Date	te		Note				
LD8017.	693-US-N	I-700-740					

Light distribution	Rated input power	Color temperature	Control	Product colors
<b>[N]</b> Narrow - NEMA Type	<b>[700]</b> 10 W	<b>[740]</b> 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
2 - 26° <b>[S]</b> Spot - NEMA Type 0 - 7° <b>[MN]</b> Medium narrow - NEMA Type 3 - 42° <b>[M]</b> Medium - NEMA Type 4 - 60°		[827] 2700 K CRI 80 [830] 3000 K CRI 80 [840] 4000 K CRI 80	<b>[0-10V]</b> 0-10V	[HM2] Dark gray[HM3] Anthracite gray[HM4] Light gray[HM5] White[HM6] Bronze[CC] Custom color (Please specify RAL code)
Accessories ( <i>To be</i> ordered separately)				
Ontical accessories				

**Optical accessories** 

[007502282]

Visor for PUNTO S