



# AQSA 0.3 m

CE UK CA IK08 IP65



LW7034.557-EN-EL-350-830-EN-C1



[EL]  
Elliptical

## Variant

|                        |               |
|------------------------|---------------|
| Light distribution     | [EL] 41x13°   |
| Delivered lumens flux  | 573 lm        |
| Rated input power      | 6 W           |
| Colour temperature     | 3000 K CRI 80 |
| Luminaire efficacy     | 95 lm/W       |
| Lamp                   | 5 LED         |
| MacAdam Ellipse        | 3 SDCM        |
| Lifetime L90B50 (hour) | >102,000      |
| Lifetime L80B50 (hour) | >102,000      |

## Options

## Technical information

|                         |                                                                           |
|-------------------------|---------------------------------------------------------------------------|
| Mounting                | Surface mountable via a bracket                                           |
| Housing                 | Corrosion resistant, extruded, marine grade aluminum housing              |
| Finishing               | Chromate conversion pretreatment followed by electrostatic powder coating |
| Fasteners               | Stainless steel (AISI 304 / EN 1.4301 grade)                              |
| Gasket                  | Liquid silicone                                                           |
| Lens / Reflector        | PMMA lens with high optical efficiency                                    |
| Glass / Diffuser        | Tempered safety glass                                                     |
| Impact protection       | IK08                                                                      |
| Ingress protection      | IP65                                                                      |
| Input voltage           | 220-240V 50/60Hz                                                          |
| Insulation class        | Class I                                                                   |
| Weight                  | 1.68 kg                                                                   |
| Driver                  | External LED driver                                                       |
| Driver surge protection | 10/6 kV                                                                   |
| Power factor            | > 0.95                                                                    |
| Through wiring          | Single cable entry                                                        |
| Operating temperature   | -40...50°C                                                                |
| Cable                   | 0.5 m of flexible cable                                                   |

|                                                   |  |             |  |                 |  |
|---------------------------------------------------|--|-------------|--|-----------------|--|
| <b>Project name</b>                               |  | <b>Type</b> |  | <b>Quantity</b> |  |
| <b>Date</b>                                       |  | <b>Note</b> |  |                 |  |
| <b>LW7034.557-EN-EL-350-830-__-EN-C1-__-__-__</b> |  |             |  |                 |  |

| Light distribution                    | Rated input power    | Colour temperature            | Control                  | Product colours                                        |
|---------------------------------------|----------------------|-------------------------------|--------------------------|--------------------------------------------------------|
| <b>[EL]</b><br>Elliptical - 41x13°    | <b>[350]</b><br>6 W  | <b>[830]</b><br>3000 K CRI 80 | <b>[ONOFF]</b><br>On/Off | <b>[HM1]</b><br>Black                                  |
| <b>[EL]</b><br>Elliptical - 147x106°  | <b>[700]</b><br>12 W | <b>[827]</b><br>2700 K CRI 80 | <b>[DALI]</b><br>DALI    | <b>[HM2]</b><br>Dark grey                              |
| <b>[N]</b><br>Narrow - 20°            |                      | <b>[740]</b><br>4000 K CRI 70 |                          | <b>[HM3]</b><br>Anthracite grey                        |
| <b>[MN]</b><br>Medium narrow - 35°    |                      | <b>[840]</b><br>4000 K CRI 80 |                          | <b>[HM4]</b><br>Light grey                             |
| <b>[M]</b><br>Medium - 65°            |                      |                               |                          | <b>[HM5]</b><br>White                                  |
|                                       |                      |                               |                          | <b>[HM6]</b><br>Bronze                                 |
|                                       |                      |                               |                          | <b>[CC]</b><br>Custom colour (Please specify RAL code) |
| Extras                                |                      |                               |                          |                                                        |
| Mounting options                      |                      |                               |                          |                                                        |
| <b>[ASB]</b><br>Angle setting bracket |                      |                               |                          |                                                        |
| <b>[LB]</b><br>Long bracket           |                      |                               |                          |                                                        |
| Consult the factory                   |                      |                               |                          |                                                        |
| <b>[UNI]</b><br>120-277V 50/60Hz      |                      |                               |                          |                                                        |