

DOGO Ex Forward






LW7035.575-EN-SLFW-350-827-EN-C1









[SLFW] Special linear, Forward throw

Variant

Light distribution [SLFW] 111x53° Delivered lumens flux 963 lm Rated input power 10 W **Colour temperature** 2700 K CRI 80 Luminaire efficacy 96 lm/W Lamp 4 LED **BUG** rating B1-U0-G1 Lifetime L90B50 (hour) >42,000 Lifetime L80B50 (hour) >42,000

Options

Technical information

Mounting	Surface or wal	I mountable with angle setting
		machanicm

mechanism +135°/0°

Tilt angle Housing Corrosion resistant, die-cast, marine grade

aluminum housing

Finishing Chromate conversion pretreatment followed by

electrostatic powder coating

Fasteners Stainless steel (AISI 304 / EN 1.4301 grade)

Silicone Gasket

High reflectance aluminium coating, Lens / Reflector

multifaceted micro reflector

Glass / Diffusor Tempered safety glass Impact protection **IK08**

Ingress protection IP65 Input voltage 220-240V 50/60Hz

Insulation class Class I 5.1 kg

Weight High power LEDs on metal-core PCB **LED** module

Driver Internal LED driver

Driver surge 1/1 kV

protection Power factor > 0.90

Through wiring Single cable entry -40...50°C Operating

temperature

Cable 0.2 m of flexible cable QUICK SHIP: Some variants will be delivered Notes faster. Please consult the factory.

Accessories (To be ordered separately)

Mounting accessories



DALI driver within an IP67 box for DOGO

007502840

Project na	me			Туре	Quantity		
Date			Note				

LW7035.575-EN-SLFW-350-827-__-EN-C1-__--_

		_		
Light distribution	Rated input power	Colour temperature	Control	Product colours
[SLFW] Special linear,	[350] 10 W	[827] 2700 K CRI 80	[ONOFF] On/Off	[HM1] Black
Forward throw - 111x53°	[700] 20 W	[822] 2200 K CRI 80	[DALI] DALI	[HM2] Dark grey
		[830] 3000 K CRI 80		[HM3] Anthracite grey
		[740] 4000 K CRI 70		[HM4] Light grey
		[840] 4000 K CRI 80		[HM5] White
				[HM6] Bronze
				[CC] Support (Custom colour (Please specify RAL code)
Extras	Accessories (To be ordered separately)			I
Consult the factory	Mounting			
[EK] Emergency kit	accessories [007502840]			
[MS] Motion sensor	DALI driver within an IP67 box for DOGO			
Luminaire body options				
[DPC] Double powder coating				