
DOGO Ex Side


се чков № 1808 № 1805 (Д)



LW7035.585-EN-SLSW-350-827-EN-C1









Special linear, Side throw

Variant

Light distribution	[SLSW] 154x55°
Delivered lumens flux	499 lm
Rated input power	5 W
Colour temperature	2700 K CRI 80
Luminaire efficacy	99 lm/W
Lamp	2 LED
BUG rating	B0-U0-G0
Lifetime L90B50 (hour)	>42,000
Lifetime L80B50 (hour)	>42,000

Options

Technical information

Mounting	Surface or wall mountable with angle setting
- "In a set of	mechanism
Tilt angle	+135°/0°
Housing	Corrosion resistant, die-cast, marine grade
	aluminum housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating,
	multifaceted micro reflector
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP65
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Wind catching area	N/A
(EPA)	
Weight	5.1 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	1/1 kV
protection	
Power factor	> 0.90
Through wiring	Single cable entry
Operating	-4050°C
temperature	
Cable	0.2 m of flexible cable
Notes	QUICK SHIP: Some variants will be delivered

QUICK SHIP: Some variants will be delivered faster. Please consult the factory.

HPR Pazarlama A.Ş. Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30

info@hepergroup.com

HEPER Europe GmbH Ahornweg 5a, 58675

Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 18.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards. 1/3

Accessories (To be ordered separately)

Mounting accessories



DALI driver within an IP67 box for DOGO

007502840

HPR Pazarlama A.Ş. Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 18.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

2/3

Project na	me				Туре	Quantity	
Date			Note				
LW7035.585-EN-SLSW-350-827EN-C1							

Light distribution	Rated input power	Colour temperature	Control	Product colours
[SLSW] Special linear, Side throw - 154x55°	[350] 5 W	[827] 2700 K CRI 80	[ONOFF] On/Off	[HM1] Black
	[700] 10 W	[822] 2200 K CRI 80 [830] 3000 K CRI 80 [740] 4000 K CRI 70	[DALI] DALI	[HM2]Dark grey[HM3]Anthracite grey[HM4]
		[840] 4000 K CRI 80		Light grey [HM5] White
				[HM6] Bronze
				[CC] (Vertical and the second specify RAL code)
Extras	Accessories (To be ordered separately)	_		
Consult the factory	Mounting accessories	_		
[EK] Emergency kit [MS] Motion sensor	[007502840] DALI driver within an IP67 box for DOGO			
Luminaire body options				
[DPC] Double powder coating				

HPR Pazarlama A.Ş. Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey

+90 312 267 54 30

info@hepergroup.com

HEPER Europe GmbH Ahornweg 5a, 58675 Hemer, Germany

+49 237 2901 2975

infoEU@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 18.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.