
DOGO Ex Side


CE UK IKO8 IP65



LW7035.585-EN-SLSW-700-840-EN-C1









Special linear, Side throw

Variant

Light distribution [SLSW] 154x55° Delivered lumens flux 1108 lm Rated input power 10 W **Colour temperature** 4000 K CRI 80 Luminaire efficacy 110 lm/W Lamp 2 LED **BUG** rating B1-U0-G1 >42,000 Lifetime L90B50 (hour) Lifetime L80B50 (hour) >42,000

Options

Technical information

mechanism

Tilt angle +135°/0° Housing Corrosion resistant, die-cast, marine grade

aluminum housing

Finishing Chromate conversion pretreatment followed by

electrostatic powder coating

Stainless steel (AISI 304 / EN 1.4301 grade)

Fasteners Silicone Gasket

High reflectance aluminium coating,

multifaceted micro reflector Glass / Diffusor

Tempered safety glass Impact protection **IK08**

Ingress protection IP65 Input voltage 220-240V 50/60Hz

Insulation class Class I Wind catching area N/A

(EPA)

Weight 5.1 kg

LED module High power LEDs on metal-core PCB Driver Internal LED driver

Driver surge 1/1 kV

protection

Lens / Reflector

> 0.90 **Power factor** Through wiring Single cable entry

-40...50°C Operating

temperature

Cable 0.2 m of flexible cable QUICK SHIP: Some variants will be delivered Notes faster. Please consult the factory.

Accessories (To be ordered separately)

Mounting accessories



DALI driver within an IP67 box for DOGO

007502840

Project name					Туре	Quantity	
Date			Note				

LW7035.585-EN-SLSW-700-840-___-EN-C1-__--_

Light distribution	Rated input power	Colour temperature	Control	Product colours	
[SLSW] Special linear, Side	[700] 10 W	[840] 4000 K CRI 80	[ONOFF] On/Off	[HM1] Black	
throw - 154x55°	[350] 5 W	[822] 2200 K CRI 80	[DALI] DALI	[HM2] Dark grey	
		[827] 2700 K CRI 80		[HM3] Anthracite grey	
		[830] 3000 K CRI 80		[HM4] Light grey	
		[740] 4000 K CRI 70		[HM5] White	
				[HM6] Bronze	
				[CC] Custom colour (Please specify RAL code)	
Extras	Accessories (To be ordered separately)				
Consult the factory	Mounting				
[EK]	accessories				
Emergency kit [MS] Motion sensor	[007502840] DALI driver within an IP67 box for DOGO				
Luminaire body options					
[DPC] Double powder coating					