

URBAN UNITS V3 Top Module, 180°, 4 Module

LP4054.847-US-ASYM-700-827







Ø7 7/8"



Asymmetric

infoUS@hepergroup.com

Configuration

Light distribution	[ASYM] 121x40°
Delivered lumens flux	4176 lm
Rated input power	52 W
Color temperature	2700 K CRI 80
Luminaire efficacy	80 lm/W
Lamp	24 LED
Color Deviation	3 SDCM
Lifetime L90 (hour)	>60,000
Lifetime L80 (hour)	>60,000

Options

Power cord

Technical inform	ation
Housing	Corrosion resistant, marine grade aluminum
	housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating,
	multifaceted micro reflector
Glass / Diffusor	UV stable, bio-based polycarbonate diffusor
Impact protection	IK08
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	34 lbs
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	6/6 kV
protection	
Power factor	> 0.95
Through wiring	Single power cord entry
Operating	-4050°C
temperature	

8" of flexible power cord

Product specific poles with base plate

	Configuration code I	Height	Diameter / Dimensions	Spigot / End diameter
	PAFC.C01.T001-H3	10'	Ø7 7/8"	
1	PAFC.C01.T001-H4	13.1'	Ø7 7/8"	
	PAFC.C01.T001-H5	16.4'	Ø7 7/8"	

Project na	me			Туре	Quantity		
Date			Note				

LP4054.847-US-ASYM-700-827-__--_

Light distribution	Rated input power	Color temperature	Control	Product colors
[ASYM] Asymmetric - 121x40°	[700] 52 W	[827] 2700 K CRI 80	[ONOFF] On/Off	[HM1] Black
		[830] 3000 K CRI 80	[0-10V] 0-10V	[HM2] Dark gray
		[740] 4000 K CRI 70		[HM3] Anthracite gray
		[840] 4000 K CRI 80		[HM4] Light gray
				[HM5] White
				[HM6] Bronze
				[CC] Custom color (Please specify RAL code)

Extras

Luminaire body options

[DPC]

Double powder coating