

REGIO IN 2 Module


CE UK CA IK08 IP66



LF8037.522-EN-N-700-840-EN-C1



PHASED-
OUT



[N]
Narrow

Variant

Light distribution	[N] 22°
Delivered lumens flux	55652 lm
Rated input power	460 W
Colour temperature	4000 K CRI 80
Luminaire efficacy	120 lm/W
Lamp	216 LED
MacAdam Ellipse	3 SDCM
Lifetime L90B50 (hour)	>102,000
Lifetime L80B50 (hour)	>102,000

Options

Technical information

Mounting	Direct tray mountable
Tilt angle	+30°/-30°
Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone rubber
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP66
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	16.64 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	10/10 kV
Power factor	> 0.99
Through wiring	Single cable entry
Operating temperature	-40...50°C
Cable	1 m of flexible cable

Project name		Type		Quantity	
Date		Note			
LF8037.522-EN-N-700-840-__-EN-C1-__-__-__					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[N] Narrow - 22°	[700] 460 W	[840] 4000 K CRI 80	[ONOFF] On/Off	[HM3] Anthracite grey 
[I] - 26°	[700] 459 W	[830] 3000 K CRI 80	[DALI] DALI	[HM4] Light grey 
[EL] Elliptical - 15x40°				[CC]  Custom colour (Please specify RAL code)
[MN] Medium narrow - 30°				
[M] Medium - 50°				
[W] Wide - 111°				
Extras				
Consult the factory				
[UNI] 120-277V 50/60Hz				
Luminaire body options				
[DPC] Double powder coating				