
NORMA


CE UK IKO5 IP65



LB6055.510-EN-SYM-4L-350-740-EN-C1









[SYM-4L] Symmetric, Special effect: 4 lines

Variant

Light distribution [SYM-4L] 120° **Delivered lumens flux** 1426 lm Rated input power 19 W **Colour temperature** 4000 K CRI 70 **Luminaire efficacy** 79 lm/W Lamp 4 LED MacAdam Ellipse 3 SDCM Lifetime L90B50 (hour) >72,600 Lifetime L80B50 (hour) >72,600

Options

Technical information

| Corrosion resistant, extruded, marine grade |
|--|
| aluminum housing |
| Chromate conversion pretreatment followed by |
| electrostatic powder coating |
| Stainless steel (AISI 304 / EN 1.4301 grade) |
| Liquid silicone |
| PMMA lens with high optical efficiency |
| Tempered safety glass |
| IK05 |
| IP65 |
| 220-240V 50/60Hz |
| Class I |
| 23 kg |
| Multi-chip high power LEDs on metal-core PCB |
| Internal LED driver |
| 6/6 kV |
| |
| > 0.95 |
| Single cable entry |
| -4050°C |
| |

temperature 0.5 m of flexible cable Cable

Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com

Accessories (To be ordered separately)

Anchorages

Flange covers





90CJ001

C3F2C.T002

90CJ001

C3F2C.T002

| Project name | | | Туре | Quantity | | |
|--------------|--|--|------|----------|--|--|
| Date | | | Note | | | |

LB6055.510-EN-SYM-4L-350-740-___-EN-C1-__--

| Light distribution | Rated input power | Colour temperature | Control | Product colours |
|--|--|---------------------------------|-------------------|--|
| [SYM-4L] Symmetric, Special effect: 4 lines - 120° | [350] 19 W | [740] 4000 K CRI 70 | [ONOFF] On/Off | [HM1] Black |
| | [700] 36 W | [827] 2700 K CRI 80 | [DALI] DALI | [HM2] Dark grey |
| | | [830] 3000 K CRI 80 | [AUTO] AutoDIM | [HM3] Anthracite grey |
| | | [840] 4000 K CRI 80 | [STEP] StepDIM | [HM4] Light grey |
| | | | | [HM5] White |
| | | | | [HM6] Bronze |
| | | | | [CC] Custom colour (Plea specify RAL code) |
| Extras | Accessories (To be ordered separately) | | | |
| Consult the factory | Anchorages | | | |
| [UNI] 120-277V 50/60Hz | [90CJ001] 90CJ001 | | | |
| Luminaire body | Flange covers | | | |
| IDPC Double powder coating | [C3F2C.T002] C3F2C.T002 | | | |