MINIMO 2x120°

CE LK IK10 IP67






LR9015.515-2x120-EN-C2-350-830-ONOFF-EN-C1









Variant

Delivered lumens flux 15 lm Rated input power 1.7 W 2700 K CRI 80 **Colour temperature Luminaire efficacy** 8 lm/W Lamp 1 LED **MacAdam Ellipse** 3 SDCM Lifetime L90B50 (hour) >102,000 Lifetime L80B50 (hour) >102,000

Options

temperature

Technical information

Mounting	Ground recessed mountable
Housing	Corrosion resistant, marine grade aluminum
	housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone rubber
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Custom Design PMMA Diffusor
Impact protection	IK10
Ingress protection	IP67
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	0.6 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	1/1 kV
protection	
Power factor	> 0.60
Through wiring	Single cable entry
Operating	-4050°C







Junction Box for MINIMO-MINIKA

Plastic case for MINIMO/MINIKA

141901034

160401101

Mounting accessories



Connector set - 5pole

141407400

Project na	me		Туре	Quantity	
Date		Note			

LR9015.515-2x120-EN-C2-350-830-ONOFF-EN-C1-__--_

Light distribution	Rated input power	Colour temperature	Control	Product colours
[] - 240x50°	[350] 1.7 W	[827] 2700 K CRI 80	[ONOFF] On/Off	[HM1] Black
[C2-120] Controlled, 2 sides, 2x120° - 240x50°		[830] 3000 K CRI 80		[HM2] Dark grey
		[740] 4000 K CRI 70		[HM3] Anthracite grey
		[840] 4000 K CRI 80		[HM4] Light grey
				[HM5] White
				[HM6] Bronze
				[CC] Custom colour (Pleas specify RAL code)
Extras	Accessories (Included)	Accessories (To be ordered separately)		
Consult the factory	Mounting	Mounting		
[UNI] 120-277V 50/60Hz	accessories [141901034]	accessories [141407400] Connector set - 5-pole	_	
Luminaire body options	Junction Box for MINIMO-MINIKA			
[SS] Stainless steel housing	Plastic case for MINIMO/MINIKA			