MINIMO 4x90°


heper to hep

LR9015.515-4x90-US-C4-350-827-ONOFF











[**C4-90**] Controlled, 4 sides, 4x90°

Configuration

Light distribution [C4-90] 360x50° Delivered lumens flux 17 lm Rated input power 1.7 W **Color temperature** 2700 K CRI 80 **Luminaire efficacy** 10 lm/W Lamp 1 LED **Color Deviation** 3 SDCM Lifetime L90 (hour) >102,000 >102,000 Lifetime L80 (hour)

Options

Technical information

Mounting Ground recessed mountable Corrosion resistant stainless steel housing Housing Finishing Chromate conversion pretreatment followed by electrostatic powder coating **Fasteners** Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Silicone rubber Lens / Reflector PMMA lens with high optical efficiency Glass / Diffusor Custom Design PMMA Diffusor Impact protection Ingress protection IP67 120-277V 50/60Hz Input voltage Class I **Insulation class** 1 lbs Weight High power LEDs on metal-core PCB LED module Driver Internal LED driver **Driver surge** 3/3 kV

protection

Power factor > 0.40
Through wiring Single power cord entry
Operating -40...50°C

temperature

Power cord 12" of rubber-sheated power cord

Accessories (Included)

Mounting accessories Mounting accessories





Connector set - 5pole

Plastic case for MINIMO/MINIKA

141407400

160401101

Project name					Туре	Quantity	
Date			Note				

LR9015.515-4x90-US-C4-350-827-ONOFF-___

Light distribution	Rated input power	Color temperature	Control	Product colors		
[C4-90] Controlled, 4 sides,	[350] 1.7 W	[827] 2700 K CRI 80	[ONOFF] On/Off	[HM1] Black		
4x90° - 360x50°		[830] 3000 K CRI 80 [740] 4000 K CRI 70 [840] 4000 K CRI 80		[HM2] Dark gray [HM3] Anthracite gray [HM4]		
				Light gray [HM5] White [HM6]		
				[CC] Custom color (Please specify RAL code)		

Accessories (*Included*)

Mounting accessories

[141407400]

Connector set - 5-pole

[160401101]

Plastic case for MINIMO/MINIKA