



MINIKA 90°



LR9014.515-90-EN-C1-350-830-ONOFF



[C1-90]

Controlled, 1 side,
90°

Configuration

Light distribution	[C1-90] 90x50°
Delivered lumens flux	7 lm
Rated input power	1.7 W
Color temperature	3000 K CRI 80
Luminaire efficacy	4 lm/W
Lamp	1 LED
Color Deviation	3 SDCM
Lifetime L90 (hour)	>102,000
Lifetime L80 (hour)	>102,000


Options

Technical information

Mounting	Ground recessed mountable
Housing	Corrosion resistant, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone rubber
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Custom Design PMMA Diffusor
Impact protection	IK10
Ingress protection	IP67
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	0.66 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	1/1 kV
Power factor	> 0.60
Through wiring	Single power cord entry
Operating temperature	-40...50°C
Power cord	12" of rubber-sheathed power cord

Accessories (Included)

Mounting accessories



Junction Box for
MINIMO-MINIKA

141901034

Mounting accessories




Plastic case for
MINIMO/MINIKA

160401101

Accessories (To be ordered separately)








Mounting accessories



Connector set - 5-
pole

141407400

Project name					Type		Quantity	
Date			Note					
LR9014.515-90-EN-C1-350-830-ONOFF-__-__-__								

Light distribution	Rated input power	Color temperature	Control	Product colors
[C1-90] Controlled, 1 side, 90° - 90x50°	[350] 1.7 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[HM1] Black 
		[827] 2700 K CRI 80		[HM2] Dark gray 
		[740] 4000 K CRI 70		[HM3] Anthracite gray 
		[840] 4000 K CRI 80		[HM4] Light gray 
				[HM5] White 
				[HM6] Bronze 
				[CC]  Custom color (Please specify RAL code)
Extras	Accessories <i>(Included)</i>	Accessories <i>(To be ordered separately)</i>		
Consult the factory	Mounting accessories	Mounting accessories		
[UNI] 120-277V 50/60Hz	[141901034] Junction Box for MINIMO-MINIKA	[141407400] Connector set - 5-pole		
Luminaire body options				
[SS] Stainless steel housing	[160401101] Plastic case for MINIMO/MINIKA			