



LR9014.515-3x90-EN-C3-350-840-ONOFF-EN-C1



[C3-90]

Controlled, 3 sides,
3x90°

Variant

Light distribution	[C3-90] 270x50°
Delivered lumens flux	19 lm
Rated input power	1.7 W
Colour temperature	4000 K CRI 80
Luminaire efficacy	11 lm/W
Lamp	1 LED
MacAdam Ellipse	4 SDCM
Lifetime L90B50 (hour)	>102,000
Lifetime L80B50 (hour)	>102,000


Options

Technical information

Mounting	Ground recessed mountable
Housing	Corrosion resistant, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone rubber
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Custom Design PMMA Diffusor
Impact protection	IK10
Ingress protection	IP67
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	0.66 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	1/1 kV
Power factor	> 0.60
Through wiring	Single cable entry
Operating temperature	-40...50°C
Cable	0.3 m of rubber-sheathed cable

Accessories (Included)

Mounting accessories



**Junction Box for
MINIMO-MINIKA**

141901034

Mounting accessories




**Plastic case for
MINIMO/MINIKA**

160401101

Accessories (To be ordered separately)

Mounting accessories



**Connector set - 5-
pole**

141407400

Project name		Type		Quantity	
Date		Note			
LR9014.515-3x90-EN-C3-350-840-ONOFF-EN-C1-__-__-__					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[C3-90] Controlled, 3 sides, 3x90° - 270x50°	[350] 1.7 W	[840] 4000 K CRI 80 [827] 2700 K CRI 80 [830] 3000 K CRI 80 [740] 4000 K CRI 70	[ONOFF] On/Off	[HM1]  Black [HM2]  Dark grey [HM3]  Anthracite grey [HM4]  Light grey [HM5]  White [HM6]  Bronze [CC]  Custom colour (Please specify RAL code)
Extras	Accessories <i>(Included)</i>	Accessories <i>(To be ordered separately)</i>		
Consult the factory	Mounting accessories	Mounting accessories		
[UNI] 120-277V 50/60Hz	[141901034] Junction Box for MINIMO-MINIKA	[141407400] Connector set - 5-pole		
Luminaire body options	[160401101] Plastic case for MINIMO/MINIKA			
[SS] Stainless steel housing				