PINA W

IK06 IP65

LW8034.003-EN-MN-927-ONOFF-EN-C1





[MN]
Medium narrow

Variant

Light distribution	[MN] 36°
Delivered lumens flux	368 lm
Rated input power	7.5 W
Colour temperature	2700 K CRI 90
Luminaire efficacy	49 lm/W
Lamp	1 LAMP
MacAdam Ellipse	5 SDCM

Options

Technical information

Mounting	Wall mountable
Housing	Corrosion resistant, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Glass / Diffusor	Tempered safety glass
Impact protection	IK06
Ingress protection	IP65
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	0.71 kg
Driver	Internal LED driver
Power factor	> 0.80
Through wiring	Single cable entry
Cable	0.2 m of flexible cable
Packing box dimensions	11*18*7 cm

HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,
Sincan, 06909 Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 237 2901 2975
infoEU@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 18.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project name		Type		Quantity	
Date		Note			

LW8034.003-EN-MN-927-ONOFF-EN-C1-__-__

Light distribution	Rated input power	Colour temperature	Control	Product colours
[MN] Medium narrow - 36°	**[]** 7.5 W	**[927]** 2700 K CRI 90	**[ONOFF]** On/Off	**[HM1]** Black
[VN] Very narrow - 10°		**[930]** 3000 K CRI 90		**[HM2]** Dark grey
[N] Narrow - 25°		**[940]** 4000 K CRI 90		**[HM3]** Anthracite grey
[M] Medium - 60°				**[HM4]** Light grey
				[HM5] White
				[HM6] Bronze
				[CC] Custom colour (Please specify RAL code)

Extras
Consult the factory
[UNI] 120-277V 50/60Hz

HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,
Sincan, 06909 Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 237 2901 2975
infoEU@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 18.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.