



IN-LIGHT ML 4 Module



LW2029.674-US-EL-500-740



PHASED-
OUT



[EL]
Elliptical

Configuration

Light distribution	[EL] 130x85°
Delivered lumens flux	11355 lm
Rated input power	95 W
Color temperature	4000 K CRI 70
Luminaire efficacy	120 lm/W
Lamp	16 LED
Color Deviation	3 SDCM
BUG rating	B3-U0-G2
Lifetime L90 (hour)	>60,000
Lifetime L80 (hour)	>60,000

Options

Technical information

Mounting	Direct tray mountable
Housing	Corrosion resistant, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating, multifaceted micro reflector
Glass / Diffusor	Bio-based, enriched with bisphenol A diffusor
Impact protection	IK08
Ingress protection	IP66
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	21.8 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	6/4 kV
Power factor	> 0.98
Through wiring	Single power cord entry
Operating temperature	-40...50°C
Power cord	40" of halogen-free power cord

Project name				Type		Quantity	
Date		Note					
LW2029.674-US-EL-500-740-__-__-__							

Light distribution	Rated input power	Color temperature	Control	Product colors
[EL] Elliptical - 130x85°	[500] 95 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
	[700] 135 W	[830] 3000 K CRI 80	[0-10V] 0-10V	[HM2] Dark gray
				[HM3] Anthracite gray
				[HM4] Light gray
				[HM5] White
				[HM6] Bronze
				[CC] Custom color (Please specify RAL code)
Extras				
Luminaire body options				
[DPC] Double powder coating				