PUNTO S

LF8017.693-US-S-700-740

[S] [N]   [MN] [M]

198 mm
7 51/64"

On/Off

Ø86 mm
Ø3 25/64"

118 mm
4 41/64"

223 mm
8 25/32"

Ø86 mm
Ø3 25/64"

1-10V, DALI

[S]
Spot - NEMA Type 0

Configuration

Light distribution	[S] 7°
Delivered lumens flux	1019 lm
Rated input power	10 W
Color temperature	4000 K CRI 70
Luminaire efficacy	101 lm/W
Lamp	1 LED
Color Deviation	5 SDCM
Lifetime L90 (hour)	>72,600
Lifetime L80 (hour)	>72,600

Options

Technical information

Mounting	Yoke mount (standard), stake mount (optional)
Tilt angle	+60°/-30°
Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone rubber
Lens / Reflector	High reflectance aluminium coating [S] [N], PMMA lens with high optical efficiency [MN] [M]
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Wind catching area (EPA)	0.23 ft²
Weight	3.3 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	1/1 kV
Power factor	> 0.90
Through wiring	Single power cord entry
Operating temperature	-30...50°C
Power cord	16" of flexible power cord

Accessories (To be ordered separately)

Optical accessories

Mounting accessories

Visor for PUNTO S

007502282

Spike

160405040

We reserve the right to change specifications without prior written notice. Edition: 18.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project name				Type		Quantity	
Date			Note				

LF8017.693-US-S-700-740-___-___-___

Light distribution	Rated input power	Color temperature	Control	Product colors	
[S] Spot - NEMA Type 0 - 7°	**[700]** 10 W	**[740]** 4000 K CRI 70	**[ONOFF]** On/Off	**[HM1]** Black	
[N] Narrow - NEMA Type 2 - 26°		**[827]** 2700 K CRI 80	**[0-10V]** 0-10V	**[HM2]** Dark gray	
[MN] Medium narrow - NEMA Type 3 - 42°		**[730]** 3000 K CRI 70		**[HM3]** Anthracite gray	
[M] Medium - NEMA Type 4 - 60°		**[830]** 3000 K CRI 80		**[HM4]** Light gray	
		[840] 4000 K CRI 80		**[HM5]** White	
				[HM6] Bronze	
				[CC] Custom color (Please specify RAL code)	

Extras	Accessories (*To be ordered separately*)
Luminaire body options	**Optical accessories**
[DPC] Double powder coating	**[007502282]** Visor for PUNTO S
	Mounting accessories
	[160405040] Spike

We reserve the right to change specifications without prior written notice. Edition: 18.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.