



C-LIGHT ML 4 Module

CE UK CA IK08 IP66



LC2029.674-EN-T5-700-830-EN-C1



[T5]

Type V, Symmetric

Variant

Light distribution	[T5] 130x100°
Delivered lumens flux	13580 lm
Rated input power	137 W
Colour temperature	3000 K CRI 80
Luminaire efficacy	99 lm/W
Lamp	16 LED
MacAdam Ellipse	5 SDCM
Photobiological safety	Risk group 0
Lifetime L90B50 (hour)	>60,000
Lifetime L80B50 (hour)	>60,000

Options

Technical information

Mounting	Catenary wire mounting
Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating, multifaceted micro reflector
Glass / Diffusor	Bio-based, enriched with bisphenol A diffusor
Impact protection	IK08
Ingress protection	IP66
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	9.6 kg
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	8/6 kV
Power factor	> 0.99
Through wiring	Single cable entry
Operating temperature	-40...50°C
Cable	1 m of halogen-free cable
Notes	This product can be supplied with Insulation class (Class II) upon request. Please contact factory.

Project name		Type		Quantity	
Date		Note			
LC2029.674-EN-T5-700-830-__-EN-C1-__-__-__					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[T5] Type V, Symmetric - 130x100°	[700] 137 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[HM3]  Anthracite grey
[T2] Type II, Asymmetric, Side throw - 130x85°		[827] 2700 K CRI 80 [740] 4000 K CRI 70 [840] 4000 K CRI 80	[DALI] DALI	[HM4]  Light grey [CC]  Custom colour (Please specify RAL code)
Extras				
Consult the factory				
[C2] Class II [UNI] 120-277V 50/60Hz				
Luminaire body options [DPC] Double powder coating				