


## **PUNTO**

# heper t

### LF8018.694-US-S-700-740









**[S]** Spot - NEMA Type 0

### Configuration

**Light distribution** [S] 7° Delivered lumens flux 2981 lm Rated input power 27 W **Color temperature** 4000 K CRI 70 **Luminaire efficacy** 115 lm/W Lamp 3 LED **Color Deviation** 5 SDCM >72,600 Lifetime L90 (hour) Lifetime L80 (hour) >72,600

## Options

#### Technical information

Mounting Yoke mount (standard), stake mount (optional) Tilt angle +60°/-30° Housing Corrosion resistant, die-cast, marine grade aluminum housing Finishing Chromate conversion pretreatment followed by electrostatic powder coating Fasteners Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Silicone rubber Lens / Reflector High reflectance aluminium coating [S] [N], PMMA lens with high optical efficiency [MN] [M] Glass / Diffusor Tempered safety glass Impact protection **IK08** Ingress protection IP65 Input voltage 120-277V 50/60Hz **Insulation class** Class I Wind catching area 0.32 ft<sup>2</sup> (EPA) Weight 9.1 lbs

Weight 9.1 lbs

LED module Multi-chip high power LEDs on metal-core PCB

Driver Internal LED driver

Driver surge 10/6 kV

protection
Power factor > 0.95
Through wiring Single power cord entry

**Operating** -40...50°C

temperature

and applicable standards.

**Power cord** 16" of flexible power cord

# Accessories (To be ordered separately)

Mounting accessories Optical accessories





Spike

**Snoot for PUNTO** 

160405040

007502216

Project na	me		Type Quantity				
Date		Note					

# LF8018.694-US-S-700-740-\_\_--\_

Light distribution	Rated input power	Color temperature	Control	Product colors
[S] Spot - NEMA Type 0 -	[ <b>700]</b> 27 W	[ <b>740]</b> 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
7°  [N] Narrow - NEMA Type 2 - 26°  [MN] Medium narrow - NEMA Type 3 - 42°  [M] Medium - NEMA Type 4 - 60°		[827] 2700 K CRI 80 [830] 3000 K CRI 80 [840] 4000 K CRI 80	[ <b>0-10V</b> ] 0-10V	[HM2] Dark gray  [HM3] Anthracite gray  [HM4] Light gray  [HM5] White  [HM6] Bronze
Extras	Accessories (To be ordered separately)			custom color (Pleas specify RAL code)
Luminaire body options	Mounting accessories			
[DPC] Double powder	<b>[160405040]</b> Spike			
coating	Optical accessories			
	[007502216] Snoot for PUNTO			