

# **VEGAS**

## LF8020.693-US-MN-700-740









[MN] Medium narrow -NEMA Type 3

# Configuration

**Light distribution** [MN] 42° **Delivered lumens flux** 738 lm 10 W Rated input power **Color temperature** 4000 K CRI 70 **Luminaire efficacy** 73 lm/W Lamp 1 LED **Color Deviation** 5 SDCM Lifetime L90 (hour) >72,600 Lifetime L80 (hour) >72,600

### Options

#### Technical information

Mounting	Yoke mount (standard), stake mount (optional)
Tilt angle	+60°/-30°
Housing	Corrosion resistant, die-cast, marine grade
	aluminum housing
Finishing	Chromate conversion pretreatment followed by
riiiisiiiiig	
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	High reflectance aluminium coating [S] [N],
	PMMA lens with high optical efficiency [MN] [M]
Glass / Diffusor	Tempered safety glass
Impact protection	IK07
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	4.5 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	1/1 kV
protection	
Power factor	> 0.90
Through wiring	Single power cord entry
Operating	-3050°C
	3630 €
temperature	

20" of outdoor use rated flexible power cord Power cord

heperlighting.com. All flux (±%7 tolerance) and power values

(±%10 tolerance) are derived following appropriate IES, CIE,

and applicable standards.

# Accessories (To be ordered separately)

Optical accessories

Mounting accessories





Visor for VEGA S 100708016

**Spike** 160405040

Project na	me		Туре	Quantity	
Date		Note			

# LF8020.693-US-MN-700-740-\_\_--\_

Light distribution	Rated input power	Color temperature	Control	Product colors
[MN] Medium narrow -	[ <b>700]</b> 10 W	[ <b>740]</b> 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
ISI Spot - NEMA Type 0 - 7°  [N]		[ <b>827</b> ] 2700 K CRI 80	<b>[0-10V]</b> 0-10V	[HM2] Dark gray
		[ <b>830]</b> 3000 K CRI 80		[HM3] Anthracite gray
Narrow - NEMA Type 2 - 26°		[ <b>840</b> ] 4000 K CRI 80		[HM4] Light gray
[M] Medium - NEMA Type 4 - 60°				[HM5] White
				[HM6] Bronze
				Custom color (Please specify RAL code)
Extras	Accessories (To be ordered separately)			
Luminaire body	Optical accessories			
<b>[DPC]</b> Double powder coating	[100708016] Visor for VEGA S			
	Mounting accessories			
	<b>[160405040]</b> Spike			