

MOLTO 2 Hybrid



IK08 IP67



LR9012.690-US-S-700-740-UNI-C1-SS



PHASED-
OUT



[S]
Spot

Variant

Light distribution	[S] 7°
Delivered lumens flux	2038 lm
Rated input power	18 W
Colour temperature	4000 K CRI 70
Luminaire efficacy	113 lm/W
Lamp	2 LED
MacAdam Ellipse	5 SDCM
Lifetime L90B50 (hour)	>72,600
Lifetime L80B50 (hour)	>72,600

Options

Technical information

Mounting	Ground recessed mountable
Housing	Corrosion resistant stainless steel housing (AISI 316L / EN 1.4571 grade)
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating
Glass / Diffuser	Tempered safety glass
Impact protection	IK08
Ingress protection	IP67
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	5.8 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	External LED driver
Driver surge protection	2/2 kV
Power factor	> 0.90
Through wiring	Single cable entry
Operating temperature	-30...50°C
Cable	0.3 m of rubber-sheathed cable


HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,
Sincan, 06909 Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 237 2901 2975
infoEU@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 19.05.2024.
For current version visit heperlighting.com. All flux (±7% tolerance) and power values (±10% tolerance) are derived following appropriate IES, CIE, and applicable standards.

Accessories (Included)


Mounting accessories



**Aluminium case
for ZETA 4 Dyno /
MOLTO 2 Hybrid**

007500582

Mounting accessories



**Connector set - 5-
pole**

141407400

Accessories (To be ordered separately)


Mounting accessories



**Case removing
vacuum**

160404012

Project name		Type		Quantity	
Date		Note			
LR9012.690-US-S-700-740-__-UNI-C1-SS					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[S] Spot - 7°	[700] 18 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[SS] Stainless steel 
[N] Narrow - 26°		[827] 2700 K CRI 80 [830] 3000 K CRI 80 [840] 4000 K CRI 80	[0-10V] 0-10V	
Accessories (Included)	Accessories (To be ordered separately)			
Mounting accessories	Mounting accessories			
[007500582] Aluminium case for ZETA 4 Dyno / MOLTO 2 Hybrid [141407400] Connector set - 5-pole	[160404012] Case removing vacuum			