


MOLTO 4 Hybrid



IK08 IP67



LR9012.695-US-N-700-830-UNI-C1-SS



PHASED-
OUT



[N]
Narrow

Variant

Light distribution	[N] 26°
Delivered lumens flux	3397 lm
Rated input power	35 W
Colour temperature	3000 K CRI 80
Luminaire efficacy	84 lm/W
Lamp	4 LED
MacAdam Ellipse	5 SDCM
Lifetime L90B50 (hour)	>72,600
Lifetime L80B50 (hour)	>72,600


Options

Technical information

Mounting	Ground recessed mountable
Housing	Corrosion resistant stainless steel housing (AISI 316L / EN 1.4571 grade)
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating
Glass / Diffuser	Tempered safety glass
Impact protection	IK08
Ingress protection	IP67
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	11.8 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	4/4 kV
Power factor	> 0.97
Through wiring	Single cable entry
Operating temperature	-40...50°C
Cable	0.3 m of rubber-sheathed cable

Accessories (Included)


Mounting accessories



**Aluminium case
for ZETA 8 Dyno /
MOLTO 4 Hybrid**

007500618

Mounting accessories



**Connector set - 5-
pole**

141407400

Accessories (To be ordered separately)


Mounting accessories



**Case removing
vacuum**

160404012

Project name					Type		Quantity	
Date			Note					
LR9012.695-US-N-700-830-__-UNI-C1-SS								

Light distribution	Rated input power	Colour temperature	Control	Product colours
[N] Narrow - 26°	[700] 35 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[SS] Stainless steel 
[S] Spot - 7°		[827] 2700 K CRI 80 [740] 4000 K CRI 70 [840] 4000 K CRI 80	[0-10V] 0-10V	
Accessories <i>(Included)</i>	Accessories (To be ordered separately)			
Mounting accessories	Mounting accessories			
[007500618] Aluminium case for ZETA 8 Dyno / MOLTO 4 Hybrid [141407400] Connector set - 5-pole	[160404012] Case removing vacuum			