


# **MOLTO 4 Hybrid**






## LR9012.695-EN-S-700-740-EN-C1-SS









[S] Spot

#### **Variant**

**Light distribution** [S] 7° **Delivered lumens flux** 4076 lm Rated input power 35 W **Colour temperature** 4000 K CRI 70 **Luminaire efficacy** 101 lm/W Lamp 4 LED MacAdam Ellipse 5 SDCM Lifetime L90B50 (hour) >72,600 Lifetime L80B50 (hour) >72,600

### Options

#### Technical information

Mounting	Ground recessed mountable
Housing	Corrosion resistant stainless steel housing (AISI
	316L / EN 1.4571 grade)
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP67
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	5.37 kg
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	External LED driver
Driver surge	4/4 kV
protection	
Power factor	> 0.97
Through wiring	Single cable entry
Operating	-4050°C
temperature	
Cable	0.3 m of rubber-sheated cable


Mounting accessories



Aluminium case for ZETA 8 Dyno / **MOLTO 4 Hybrid** 

007500618

Mounting accessories



Mounting accessories Mounting accessories



Case removing vacuum

160404012



Connector set - 5pole

141407400



**Junction Box** 

141901135

Project na	me		Туре	Quantity	
Date		Note			

# LR9012.695-EN-S-700-740-\_\_\_-EN-C1-SS-\_\_\_

Light distribution	Rated input power	Colour temperature	Control	Product colours
<b>[S]</b> Spot - 7°	[ <b>700</b> ] 35 W	[ <b>740]</b> 4000 K CRI 70	[ONOFF] On/Off	[SS] Stainless steel
<b>[N]</b> Narrow - 26°		[ <b>827</b> ] 2700 K CRI 80	[DALI] DALI	
		[830] 3000 K CRI 80		
		[840] 4000 K CRI 80		
Extras	Accessories (Included)	Accessories (To be ordered separately)		
Consult the factory	Mounting	Mounting		
[UNI]	accessories	accessories	_	
120-277V 50/60Hz	[007500618] Aluminium case for ZETA 8 Dyno / MOLTO	[160404012] Case removing vacuum		
	4 Hybrid	[141407400] Connector set - 5-pole		
		[141901135] Junction Box		