

MOLTO 6 Hybrid


CE UK IKO8 IP67




LR9012.697-EN-N-700-740-ONOFF-EN-C1-SS









Variant

Light distribution [N] 26° Delivered lumens flux 6052 lm Rated input power 50 W **Colour temperature** 4000 K CRI 70 Luminaire efficacy 121 lm/W Lamp 6 LED MacAdam Ellipse 5 SDCM >72,600 Lifetime L90B50 (hour) Lifetime L80B50 (hour) >72,600

Options

Technical information

Mounting Ground recessed mountable Corrosion resistant stainless steel housing (AISI Housing 316L / EN 1.4571 grade) Stainless steel (AISI 304 / EN 1.4301 grade) **Fasteners** Gasket Silicone Lens / Reflector High reflectance aluminium coating Glass / Diffusor Tempered safety glass Impact protection **IK08** Ingress protection IP67 Input voltage 220-240V 50/60Hz **Insulation class** Class I 7.75 kg Weight Multi-chip high power LEDs on metal-core PCB **LED** module External LED driver Driver **Driver surge** 4/4 kV protection **Power factor** > 0.97 Through wiring Single cable entry

Operating temperature

Cable 0.3 m of rubber-sheated cable

-40...50°C

Mounting accessories



Aluminium case for ZETA 12 Dyno / MOLTO 6 Hybrid

007500402

Mounting accessories





Case removing vacuum

160404012

Connector set - 5pole

141407400

Junction Box 141901135

Project na	me		Туре	Quantity	
Date		Note			

LR9012.697-EN-N-700-740-ONOFF-EN-C1-SS-_

Light distribution	Rated input power	Colour temperature	Control	Pro
[N] Narrow - 26°	[700] 50 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[SS] Stair
[S] Spot - 7°		[827] 2700 K CRI 80		
		[830] 3000 K CRI 80		
		[840] 4000 K CRI 80		
Extras	Accessories (Included)	Accessories (To be ordered separately)		
Consult the factory	Mounting accessories	Mounting accessories		
[UNI] 120-277V 50/60Hz	[007500402] Aluminium case for ZETA 12 Dyno / MOLTO 6 Hybrid	[160404012] Case removing vacuum [141407400] Connector set - 5-pole [141901135] Junction Box		