
PUNTO S Ex

heper

LF8030.693-US-M-700-740









[M] Medium - NEMA Type 4

Configuration

Light distribution [M] 60° Delivered lumens flux 738 lm Rated input power 10 W **Color temperature** 4000 K CRI 70 **Luminaire efficacy** 73 lm/W Lamp 1 LED **Color Deviation** 5 SDCM Lifetime L90 (hour) >72,600 Lifetime L80 (hour) >72,600

Options

Technical information

MountingPedestal knuckle mountTilt angle+60°/-30°HousingCorrosion resistant, die-cast, marine grade
aluminum housingFinishingChromate conversion pretreatment followed by
electrostatic powder coatingFastenersStainless steel (AISI 304 / EN 1.4301 grade)

Gasket Silicone rubber
Lens / Reflector High reflectance aluminium coating [S] [N],
PMMA lens with high optical efficiency [MN] [M]

Glass / Diffusor Tempered safety glass Impact protection IK08 Ingress protection IP65

Input voltage120-277V 50/60HzInsulation classClass IWeight3 lbs

LED moduleMulti-chip high power LEDs on metal-core PCBDriverInternal LED driverDriver surge1/1 kV

protection

Power factor> 0.90Through wiringSingle power cord entryPower cord16" of flexible power cord

and applicable standards.

Accessories (To be ordered separately)

Optical accessories



Visor for PUNTO S

007502282

Project na	roject name				Туре	Quantity	
Date			Note				

LF8030.693-US-M-700-740-__--_

Light distribution	Rated input power	Color temperature	Control	Product colors
[M] Medium - NEMA Type	[700] 10 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
4 - 60° [S] Spot - NEMA Type 0 -		[827] 2700 K CRI 80	[0-10V] 0-10V	[HM2] Dark gray
7° [N]		[830] 3000 K CRI 80		[HM3] Anthracite gray
Narrow - NEMA Type 2 - 26°		[840] 4000 K CRI 80		[HM4] Light gray
[MN] Medium narrow - NEMA Type 3 - 42°				[HM5] White
				[HM6] Bronze
				[CC] Custom color (Please specify RAL code)
Extras	Accessories (To be ordered separately)			I
Luminaire body	Optical accessories			
[DPC] Double powder coating	[007502282] Visor for PUNTO S			