
PUNTO S Ex

heper, t

LF8030.693-US-MN-700-740









[MN] Medium narrow -NEMA Type 3

Configuration

Light distribution [MN] 42° Delivered lumens flux 738 lm Rated input power 10 W **Color temperature** 4000 K CRI 70 **Luminaire efficacy** 73 lm/W Lamp 1 LED **Color Deviation** 5 SDCM Lifetime L90 (hour) >72,600 Lifetime L80 (hour) >72,600

Options

Power cord

Technical information

Mounting Pedestal knuckle mount
Tilt angle +60°/-30°
Housing Corrosion resistant, die-cast, marine grade
aluminum housing
Finishing Chromate conversion pretreatment followed by
electrostatic powder coating
Fasteners Stainless steel (AISI 304 / EN 1.4301 grade)

Gasket Silicone rubber
Lens / Reflector High reflectance aluminium coating [S] [N],
PMMA lens with high optical efficiency [MN] [M]

Glass / DiffusorTempered safety glassImpact protectionIK08Ingress protectionIP65

Input voltage120-277V 50/60HzInsulation classClass IWeight3 lbs

LED moduleMulti-chip high power LEDs on metal-core PCBDriverInternal LED driverDriver surge1/1 kV

protection
Power factor > 0.90
Through wiring Single power cord entry

(±%10 tolerance) are derived following appropriate IES, CIE,

and applicable standards.

16" of flexible power cord

Accessories (To be ordered separately)

Optical accessories



Visor for PUNTO S

007502282

Project name					Туре	Quantity	
Date			Note				

LF8030.693-US-MN-700-740-__--_

Light distribution	Rated input power	Color temperature	Control	Product colors
[MN] Medium narrow -	[700] 10 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
NEMA Type 3 - 42° [S] Spot - NEMA Type 0 -		[827] 2700 K CRI 80	[0-10V] 0-10V	[HM2] Dark gray
7° [N]		[830] 3000 K CRI 80		[HM3] Anthracite gray
Narrow - NEMA Type 2 - 26°		[840] 4000 K CRI 80		[HM4] Light gray
[M] Medium - NEMA Type 4 - 60°				[HM5] White
				[HM6] Bronze
				Custom color (Pleas specify RAL code)
Extras	Accessories (To be ordered separately)			
Luminaire body	Optical accessories			
[DPC] Double powder coating	[007502282] Visor for PUNTO S			