




# T-LIGHT ML 4 CB Module



LT2029.651-US-T-CB-C-700-830



PHASED-  
OUT



[T-CB-C]  
Tunnel, Counter  
beam, Type C

## Configuration








Light distribution	[T-CB-C] 130x85°
Delivered lumens flux	7554 lm
Rated input power	70 W
Color temperature	3000 K CRI 80
Luminaire efficacy	108 lm/W
Lamp	8 LED
Color Deviation	3 SDCM
BUG rating	B2-U0-G1
Photobiological safety	Risk group 0
Lifetime L90 (hour)	>72,600
Lifetime L80 (hour)	>72,600

## Options

## Technical information

Mounting	Direct tray mountable
Housing	Corrosion resistant, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating, multifaceted micro reflector
Glass / Diffuser	Bio-based, enriched with bisphenol A diffuser
Impact protection	IK08
Ingress protection	IP66
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	12.4 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	6/4 kV
Power factor	> 0.98
Through wiring	Single power cord entry
Operating temperature	-40...50°C
Power cord	40" of halogen-free power cord

Project name					Type		Quantity	
Date			Note					
LT2029.651-US-T-CB-C-700-830-__-__-__								

Light distribution	Rated input power	Color temperature	Control	Product colors
<b>[T-CB-C]</b> Tunnel, Counter beam, Type C - 130x85°	<b>[700]</b> 70 W	<b>[830]</b> 3000 K CRI 80	<b>[ONOFF]</b> On/Off	<b>[HM1]</b>  Black
		<b>[740]</b> 4000 K CRI 70	<b>[0-10V]</b> 0-10V	<b>[HM2]</b>  Dark gray <b>[HM3]</b>  Anthracite gray <b>[HM4]</b>  Light gray <b>[HM5]</b>  White <b>[HM6]</b>  Bronze <b>[CC]</b>  Custom color (Please specify RAL code)
Extras				
Luminaire body options				
<b>[DPC]</b> Double powder coating				