

VEGAS

heper, t

LF8020.693-US-N-700-740









Narrow - NEMA Type 2

Configuration

Light distribution [N] 26° **Delivered lumens flux** 1019 lm 10 W Rated input power **Color temperature** 4000 K CRI 70 **Luminaire efficacy** 101 lm/W Lamp 1 LED **Color Deviation** 5 SDCM Lifetime L90 (hour) >72,600 Lifetime L80 (hour) >72,600

Options

temperature

Technical information

Yoke mount (standard), stake mount (optional)
+60°/-30°
Corrosion resistant, die-cast, marine grade
aluminum housing
Chromate conversion pretreatment followed by
electrostatic powder coating
Stainless steel (AISI 304 / EN 1.4301 grade)
Liquid silicone
High reflectance aluminium coating [S] [N],
PMMA lens with high optical efficiency [MN] [M]
Tempered safety glass
IK07
IP65
120-277V 50/60Hz
Class I
4.5 lbs
Multi-chip high power LEDs on metal-core PCB
Internal LED driver
1/1 kV
> 0.90
Single power cord entry
-3050°C

Power cord 20" of outdoor use rated flexible power cord

Accessories (To be ordered separately)

Optical accessories

Mounting accessories





Visor for VEGA S

100708016

Spike 160405040

Project name			Туре	Quantity		
Date			Note			

LF8020.693-US-N-700-740-__--__-

Light distribution	Rated input power	Color temperature	Control	Product colors
[N] Narrow - NEMA Type	[700] 10 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
2 - 26° [S] Spot - NEMA Type 0 - 7° [MN] Medium narrow - NEMA Type 3 - 42° [M] Medium - NEMA Type 4 - 60°		[827] 2700 K CRI 80 [830] 3000 K CRI 80 [840] 4000 K CRI 80	[0-10V] 0-10V	[HM2] Dark gray [HM3] Anthracite gray [HM4] Light gray [HM5] White [HM6] Bronze [CC] Custom color (Please
Extras Luminaire body	Accessories (To be ordered separately) Optical accessories			specify RAL code)
IDPC] Double powder	[100708016] Visor for VEGA S			
coating	Mounting accessories			
	[160405040] Spike			