




C-LIGHT ML 2 Module



LC2029.672-EN-T2-700-740



[T2]
Type II

Configuration




Light distribution	[T2] 130x85°
Delivered lumens flux	6897 lm
Rated input power	68 W
Color temperature	4000 K CRI 70
Luminaire efficacy	98 lm/W
Lamp	8 LED
Color Deviation	5 SDCM
BUG rating	B2-U0-G1
Photobiological safety	Risk group 0
Lifetime L90 (hour)	>60,000
Lifetime L80 (hour)	>60,000

Options

Technical information

Mounting	Catenary wire mounting
Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating, multifaceted micro reflector
Glass / Diffusor	Bio-based, enriched with bisphenol A diffusor
Impact protection	IK08
Ingress protection	IP66
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	3.65 kg
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	10/6 kV
Power factor	> 0.95
Through wiring	Single power cord entry
Operating temperature	-40...50°C
Power cord	40" of halogen-free power cord
Notes	This product can be supplied with Insulation class (Class II) upon request. Please contact factory.

Project name				Type		Quantity	
Date		Note					
LC2029.672-EN-T2-700-740-__-__-__-__							

Light distribution	Rated input power	Color temperature	Control	Product colors
[T2] Type II - 130x85°	[700] 68 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM3]  Anthracite gray
[T5] Type V - 130x108°		[827] 2700 K CRI 80 [830] 3000 K CRI 80 [840] 4000 K CRI 80	[DALI] DALI [AUTO] AutoDIM [STEP] StepDIM	[HM4]  Light gray [CC]  Custom color (Please specify RAL code)
Extras				
Consult the factory				
[C2] Class II [UNI] 120-277V 50/60Hz				
Luminaire body options				
[DPC] Double powder coating				