


# GOLEDO-T 48 LED



LT2037.883-EN-T-SYM-D-350-730



[T-SYM-D]

Tunnel, Symmetric,  
Type D

## Configuration



Light distribution	[T-SYM-D]
Delivered lumens flux	7057 lm
Rated input power	47 W
Color temperature	3000 K CRI 70
Luminaire efficacy	152 lm/W
Lamp	48 LED
Color Deviation	4 SDCM
Lifetime L90 (hour)	>102,000
Lifetime L80 (hour)	>102,000

## Options

## Technical information

Mounting	Standard strap connection. Sliding mounting bracket is optional through extra
Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP66
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	9.01 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	10/6 kV
Power factor	> 0.95
Through wiring	Single power cord entry
Operating temperature	-40...50°C
Power cord	40" of halogen-free power cord
Notes	This product can be supplied with Insulation class (Class II) upon request. Please contact factory.

Project name					Type		Quantity	
Date			Note					
LT2037.883-EN-T-SYM-D-350-730-__-__-__-__-__-__								

Light distribution	Rated input power	Color temperature	Control	Product colors		
<b>[T-SYM-D]</b> Tunnel, Symmetric, Type D	<b>[350]</b> 47 W	<b>[730]</b> 3000 K CRI 70	<b>[ONOFF]</b> On/Off	<b>[CC]</b>  Custom color (Please specify RAL code)		
<b>[T-ASYM-A]</b> Tunnel, Asymmetric, Type A	<b>[350]</b> 51 W	<b>[740]</b> 4000 K CRI 70	<b>[0-10V]</b> 0-10V	<b>[7035]</b>  Light gray (RAL 7035)		
<b>[T-ASYM-B]</b> Tunnel, Asymmetric, Type B	<b>[500]</b> 73 W		<b>[DALI]</b> DALI			
<b>[T-ASYM-C]</b> Tunnel, Asymmetric, Type C	<b>[700]</b> 103 W		<b>[AUTO]</b> AutoDIM			
<b>[T-ASYM-D]</b> Tunnel, Asymmetric, Type D	<b>[350]</b> 46 W		<b>[STEP]</b> StepDIM			
<b>[T-ASYM-D]</b> Tunnel, Asymmetric, Type D	<b>[500]</b> 69 W					
<b>[T-CB-A]</b> Tunnel, Counter beam, Type A	<b>[500]</b> 74 W					
<b>[T-CB-B]</b> Tunnel, Counter beam, Type B	<b>[350]</b> 52 W					
<b>[T-SYM-A]</b> Tunnel, Symmetric, Type A						
<b>[T-SYM-B]</b> Tunnel, Symmetric, Type B						
<b>[T-SYM-C]</b> Tunnel, Symmetric, Type C						
<b>Extras</b>						

<b>External surge protection</b>
<b>[SP10]</b> 10 kV
<b>Light output</b>
<b>[CLO]</b> Constant light output
<b>Consult the factory</b>
<b>[C2]</b> Class II
<b>[UNI]</b> 120-277V 50/60Hz
<b>Luminaire body options</b>
<b>[DPC]</b> Double powder coating