


GOLEDO-T 32 LED



LT2037.761-US-T-ASYM-A-700-740



[T-ASYM-A]
Tunnel, Asymmetric,
Type A

Configuration

Light distribution	[T-ASYM-A]
Delivered lumens flux	10265 lm
Rated input power	68 W
Color temperature	4000 K CRI 70
Luminaire efficacy	151 lm/W
Lamp	32 LED
Color Deviation	4 SDCM
BUG rating	B3-U0-G3
Lifetime L90 (hour)	>102,000
Lifetime L80 (hour)	>102,000



Options

Technical information

Mounting	Standard strap connection. Sliding mounting bracket is optional through extra
Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP66
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	19.5 lbs
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	6/4 kV
Power factor	> 0.98
Through wiring	Single power cord entry
Operating temperature	-40...50°C
Power cord	40" of halogen-free power cord

Project name				Type		Quantity	
Date		Note					

LT2037.761-US-T-ASYM-A-700-740-

Light distribution	Rated input power	Color temperature	Control	Product colors
<div> [T-ASYM-A] Tunnel, Asymmetric, Type A </div> <div> [T-ASYM-B] Tunnel, Asymmetric, Type B </div> <div> [T-ASYM-C] Tunnel, Asymmetric, Type C </div> <div> [T-ASYM-D] Tunnel, Asymmetric, Type D </div> <div> [T-CB-A] Tunnel, Counter beam, Type A </div> <div> [T-CB-B] Tunnel, Counter beam, Type B </div> <div> [T-SYM-A] Tunnel, Symmetric, Type A </div> <div> [T-SYM-B] Tunnel, Symmetric, Type B </div> <div> [T-SYM-C] Tunnel, Symmetric, Type C </div> <div> [T-SYM-D] Tunnel, Symmetric, Type D </div>	<div> [700] 68 W </div> <div> [500] 47 W </div> <div> [500] 45 W </div> <div> [500] 46 W </div>	<div> [740] 4000 K CRI 70 </div> <div> [730] 3000 K CRI 70 </div>	<div> [ONOFF] On/Off </div> <div> [0-10V] 0-10V </div>	<div> [CC]  Custom color (Please specify RAL code) </div> <div> [7035]  Light gray (RAL 7035) </div>
Extras				
External surge protection				
[SP10] 10 kV				
Luminaire body options				
[DPC] Double powder coating				