


GOLEDO-T 64 LED

UL US IK08 IP66



LT2037.767-US-T-SYM-A-700-740-UNI-C1



[T-SYM-A]

Tunnel, Symmetric,
Type A

Variant

Light distribution	[T-SYM-A]
Delivered lumens flux	20375 lm
Rated input power	137 W
Colour temperature	4000 K CRI 70
Luminaire efficacy	148 lm/W
Lamp	64 LED
MacAdam Ellipse	4 SDCM
Lifetime L90B50 (hour)	>102,000
Lifetime L80B50 (hour)	>102,000

Options

Technical information

Mounting	Standard strap connection. Sliding mounting bracket is optional through extra
Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP66
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	20.7 lbs
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	6/4 kV
Power factor	> 0.98
Through wiring	Single cable entry
Operating temperature	-40...50°C
Cable	1 m of halogen-free cable

Project name		Type		Quantity	
Date		Note			
LT2037.767-US-T-SYM-A-700-740-__-UNI-C1-__-__-__					

Light distribution	Rated input power	Colour temperature	Control	Product colours			
[T-SYM-A] Tunnel, Symmetric, Type A	[700] 137 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[CC]  Custom colour (Please specify RAL code)			
[T-ASYM-A] Tunnel, Asymmetric, Type A	[500] 142 W	[730] 3000 K CRI 70	[0-10V] 0-10V	[7035]  Light grey (RAL 7035)			
[T-ASYM-B] Tunnel, Asymmetric, Type B	[500] 92 W						
[T-ASYM-C] Tunnel, Asymmetric, Type C	[500] 139 W						
[T-ASYM-D] Tunnel, Asymmetric, Type D	[500] 91 W						
[T-ASYM-D] Tunnel, Asymmetric, Type D	[500] 141 W						
[T-CB-A] Tunnel, Counter beam, Type A	[350] 62 W						
[T-CB-B] Tunnel, Counter beam, Type B	[350] 96 W						
[T-CB-B] Tunnel, Counter beam, Type B	[350] 95 W						
[T-SYM-B] Tunnel, Symmetric, Type B	[500] 138 W						
[T-SYM-B] Tunnel, Symmetric, Type B	[500] 143 W						
[T-SYM-C] Tunnel, Symmetric, Type C	[350] 94 W						
[T-SYM-D] Tunnel, Symmetric, Type D	[350] 97 W						
[T-SYM-D] Tunnel, Symmetric, Type D	[350] 97 W						
Extras							
External surge protection							
[SP10] 10 kV							
Luminaire body options							
[DPC] Double powder coating							