
Round tapered aluminum pole (direct burial) - Ø4 1/2"



PABK.D114-S76-H3



Configuration

Diameter / Dimensions (D)	Ø4 1/2"
Thickness	0.1"
Spigot / End diameter (S)	Ø3"
Height (H)	10'
Weight	28.2 lb
SL	5.91'
AD	15 3/4 x 3 11 11/32"
OP	19 11/16"
PD	1.97'
CD	5.9x2.9"
СР	19 11/16"

Options

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com

Accessories (To be ordered separately)

PTCD

Mounting arms	Mounting arms
Ū IP	
Mounting arm - 1 side	Mounting arm - 2 sides

PTCS

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 18.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project name			Туре	Quantity
Date	Note			
PABK.D114-S	76-Н3			
Spigot / End diameter (S)	Height (H)	Product colors	Extras	Accessories
[S76]	[H3]	[HM1] Black	LED Caps	To be ordered
Ø3"	10'		[LC1] LED caps for pole top (Circular)	separately
[S60] Ø2 3/8"	[H4] 13.1'	[HM2] Dark gray		Mounting arms [PTCS]
	[H5] 16.4'[HM3][LC2] LED caps for pole to	[LC2] LED caps for pole top (Triangle)	Mounting arm - 1 side [PTCD]	
		[HM4]	[HM4] Spigot converter Light gray [SC1] [HM5] 3" to 2 3/8" White Spigot converter [HM6] Substrate Bronze Substrate [CC] Substrate Custom color (Please Substrate	- Mounting arm - 2 sides
		[HM5] White		
		[HM6] Bronze		
		[CC] Specify RAL code)		