
## Round tapered aluminum pole (direct burial) - Ø4 3/4"



PABK.D122-S60-H6



## Configuration

Diameter / Dimensions (D)	Ø5"
Thickness	0.1"
Spigot / End diameter (S)	Ø2 3/8"
Height (H)	19.7'
Weight	45.6 lb
SL	5.91'
AD	15 3/4 x 3.5"
OP	19 11/16"
PD	3.3'
CD	5.9x2.9"
СР	19 11/16"

Options

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com

## Accessories (To be ordered separately)

PTCD

Mounting arms	Mounting arms
Ū I S	
Mounting arm - 1 side	Mounting arm - 2 sides

PTCS

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 04.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project name			Туре	Quantity
Date	Note		· ·	· · ·
PABK.D122-S	60-H6			
Spigot / End diameter (S)	Height (H)	Product colors	Extras	Accessories
[S60]	[H6]	[НМ1]	LED Caps	To be ordered
Ø2 3/8" [ <b>S76</b> ]	19.7' [H4]	Black[LC1][HM2]LED caps for pole to (Circular)Dark gray[LC2][HM3]LED caps for pole to (Triangle)[HM4]Spigot converter	LED caps for pole top	separately Mounting arms
Ø3" 13.1' [H5] 16.4' [H7] 23.0'	[H5]		[LC2]	[PTCS] Mounting arm - 1 side [PTCD] Mounting arm - 2 sides
			Spigot converter	
		[HM5] White	<b>[SC3]</b> 2 3/8" to 2"	
		[HM6] Bronze		
		[CC] (Please specify RAL code)		