
Round tapered aluminum pole (direct burial) - Ø6 1/2"



PABK.D165-S76-H7



Configuration

Diameter / Dimensions (D)	Ø6 1/2"
Thickness	0.1"
Spigot / End diameter (S)	Ø3"
Height (H)	23.0'
Weight	67.6 lb
SL	5.91'
AD	15 3/4 x 3.5"
OP	19 11/16"
PD	3.94'
CD	5.9x2.9"
СР	19 11/16"

Options

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com

Accessories (To be ordered separately)

PTCD

Mounting arms	Mounting arms
Ū I S	
Mounting arm - 1 side	Mounting arm - 2 sides

PTCS

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 11.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project name			Туре	Quantity
Date	Note		· · ·	· · ·
PABK.D165-S7	′6-H7			
Spigot / End diameter (S)	Height (H)	Product colors	Extras	Accessories
[\$76]	[H7]	[НМ1]	LED Caps	To be ordered
Ø3" [S90]	23.0' [H6]	Black [HM2]	[LC1] LED caps for pole top (Circular)	Separately Mounting arms
Ø3 1/2"	19.7'	Dark gray		[PTCS]
[H9]	[H8] 26.2'	[HM3] Anthracite gray	[LC2] LED caps for pole top (Triangle)	Mounting arm - 1 side [PTCD]
	[H9] 29.5'	[HM4] Light gray	Spigot converter	- Mounting arm - 2 sides
		[HM5] White	[SC1] 3" to 2 3/8"	
		[HM6] Bronze		
		[CC] (Please specify RAL code)	2	