
Round tapered aluminum pole (direct burial) - Ø5 7/8"



PABK.D148-S76-H7



Configuration

Diameter / Dimensions (D)	Ø6"
Thickness	0.1"
Spigot / End diameter (S)	Ø3"
Height (H)	23.0'
Weight	61.7 lb
SL	5.91'
AD	15 3/4 x 3.5"
OP	19 11/16"
PD	3.94'
CD	5.9x2.9"
СР	19 11/16"

Options

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com

Accessories (To be ordered separately)

PTCS

Mounting arms	Mounting arms	
	Γ Γ Γ Γ Γ	
Mounting arm - 2 sides	Mounting arm - 1 side	

PTCD

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 17.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project name			Туре	Quantity
Date	Note		· ·	· · ·
PABK.D148-S	76-H7			
Spigot / End diameter (S)	Height (H)	Product colors	Extras	Accessories
[S76]	[H7]	[HM1]	LED Caps	To be ordered
Ø3"	23.0'	Black	[LC1]separatelyLED caps for pole top (Circular)Mounting arms[LC2]Mounting arm - sidesLED caps for pole top (Triangle)sides	
[S60] Ø2 3/8"	[H6] 19.7'	[HM2] Dark gray		
	[H8] 26.2'	[HM3] Anthracite gray		Mounting arm - 2 sides
		[HM4] Spigot converter		[PTCS] Mounting arm - 1 side
		[HM5] White	[SC1] 3" to 2 3/8"	
		[HM6] Bronze		
		[CC] (Please specify RAL code)		