


LW7035.585-EN-SLSW-350-822-EN-C1



[SLSW]

Special linear, Side throw

## Variant

Light distribution	[SLSW] 154x55°
Delivered lumens flux	585 lm
Rated input power	5 W
Colour temperature	4000 K CRI 70
Luminaire efficacy	109 lm/W
Lamp	2 LED
BUG rating	B0-U0-G0
Lifetime L90B50 (hour)	>42,000
Lifetime L80B50 (hour)	>42,000

## Options

## Technical information

Mounting	Surface or wall mountable with angle setting mechanism
Tilt angle	+135°/0°
Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating, multifaceted micro reflector
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP65
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Wind catching area (EPA)	N/A
Weight	5.1 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	1/1 kV
Power factor	> 0.90
Through wiring	Single cable entry
Operating temperature	-40...50°C
Cable	0.2 m of flexible cable
Notes	QUICK SHIP: Some variants will be delivered faster. Please consult the factory.

## Accessories (To be ordered separately)

---








### Mounting accessories



**DALI driver within  
an IP67 box for  
DOGO**

007502840

Project name		Type		Quantity	
Date		Note			
LW7035.585-EN-SLSW-350-822-__-EN-C1-__-__-__					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[SLSW] Special linear, Side throw - 154x55°	[350] 5 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black 
	[700] 10 W	[822] 2200 K CRI 80  [827] 2700 K CRI 80  [830] 3000 K CRI 80  [840] 4000 K CRI 80	[DALI] DALI	[HM2] Dark grey   [HM3] Anthracite grey   [HM4] Light grey   [HM5] White   [HM6] Bronze   [CC]  Custom colour (Please specify RAL code)
Extras	Accessories ( <i>To be ordered separately</i> )			
Consult the factory	Mounting accessories			
[EK] Emergency kit	[007502840] DALI driver within an IP67 box for DOGO			
[MS] Motion sensor				
Luminaire body options				
[DPC] Double powder coating				