
C-LIGHT AFX 4 Module

LC2029.864-EN-T5-500-827





758 mm29 27/32"





[T5] Type V

Configuration

Light distribution [T5] 117° Delivered lumens flux 11815 lm Rated input power 97 W **Color temperature** 2700 K CRI 80 **Luminaire efficacy** 118 lm/W Lamp 64 LED **Color Deviation** 3 SDCM B3-U0-G1 **BUG** rating Lifetime L90 (hour) >102,000 Lifetime L80 (hour) >102,000

Options

Technical information

MountingCatenary wire mountingHousingCorrosion resistant, die-cast, marine grade
aluminum housing

Finishing Chromate conversion pretreatment followed by electrostatic powder coating

electrostatic powder coating

FastenersStainless steel (AISI 304 / EN 1.4301 grade)GasketLiquid siliconeLens / ReflectorPMMA lens with high optical efficiency

Glass / Diffusor Tempered safety glass Impact protection IK08 Ingress protection IP66 Input voltage 220-240V 50/60Hz

Insulation classClass IWeight8.8 kg

Weight 8.8 kg
LED module High power LEDs on metal-core PCB
Driver Internal LED driver
Driver surge 10/6 kV

protection

Power factor > 0.95
Through wiring Single power cord entry
Operating -40...50°C

temperature

Power cord 20" of outdoor use rated flexible power cord

Packing box 80*20*25 cm

dimensions

Notes This product can be supplied with Insulation

class (Class II) upon request. Please contact

factory.

and applicable standards.

| Project name | | | | | Туре | Quantity | |
|--------------|--|--|------|--|------|----------|--|
| Date | | | Note | | | | |

LC2029.864-EN-T5-500-827-__--_--

| Light distribution | Rated input power | Color temperature | Control | Product colors |
|------------------------------|---|---|-------------------|--|
| [T5] Type V - 117° | [500] 97 W | [827] 2700 K CRI 80 | [ONOFF] On/Off | [HM3] Anthracite gray |
| | [700] 135 W [350] | [830] 3000 K CRI 80 [740] | [DALI] DALI | [HM4] Light gray |
| | 68 W | 4000 K CRI 70 [840] 4000 K CRI 80 | | Custom color (Please specify RAL code) |
| | | | | |

Extras

Consult the factory

[C2]

Class II

[UNI]

120-277V 50/60Hz

Luminaire body options

[DPC]

Double powder coating