
C-LIGHT AFX 4 Module

LC2029.864-EN-T5-700-740











Type V

Configuration

Light distribution [T5] 117° Delivered lumens flux 18085 lm Rated input power 135 W **Color temperature** 4000 K CRI 70 **Luminaire efficacy** 130 lm/W Lamp 64 LED **Color Deviation** 4 SDCM B4-U1-G1 **BUG** rating Lifetime L90 (hour) >102,000 Lifetime L80 (hour) >102,000

Options

Technical information

Mounting Catenary wire mounting Housing Corrosion resistant, die-cast, marine grade aluminum housing

Finishing Chromate conversion pretreatment followed by

electrostatic powder coating

Fasteners Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Liquid silicone Lens / Reflector PMMA lens with high optical efficiency

Glass / Diffusor Tempered safety glass Impact protection Ingress protection IP66

Input voltage 220-240V 50/60Hz **Insulation class** Class I

Weight 8.8 kg High power LEDs on metal-core PCB LED module

Driver Internal LED driver 10/6 kV

Driver surge protection

Power factor > 0.95 Through wiring Single power cord entry

Operating temperature

Power cord 20" of outdoor use rated flexible power cord

Packing box

dimensions

This product can be supplied with Insulation Notes

class (Class II) upon request. Please contact

factory.

-40...50°C

80*20*25 cm

Project name				Туре	Quantity		
Date			Note				

LC2029.864-EN-T5-700-740-__--_--

[T5] [700] [740] [ONOFF] [HM3] Type V - 117° 135 W 4000 K CRI 70 On/Off Anthracite gray	Light distribution	Rated input power	Color temperature	Control	Product colors
read read read					_
97 W 2700 K CRI 80 DALI Light gray [350] [830] [CC] 68 W 3000 K CRI 80 Custom color (PI		[350]	[830] 3000 K CRI 80 [840]	[DALI] DALI	[HM4] Light gray

Extras

Consult the factory

[C2]

Class II

[UNI]

120-277V 50/60Hz

Luminaire body options

[DPC]

Double powder coating