




C-LIGHT AFX 4 Module



LC2029.864-US-T5-700-740



[T5]
Type V

Configuration




Light distribution	[T5] 117°
Delivered lumens flux	18085 lm
Rated input power	135 W
Color temperature	4000 K CRI 70
Luminaire efficacy	130 lm/W
Lamp	64 LED
Color Deviation	4 SDCM
BUG rating	B4-U1-G1
Lifetime L90 (hour)	>102,000
Lifetime L80 (hour)	>102,000

Options

Technical information

Mounting	Catenary wire mounting
Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP66
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	19.36 lbs
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	10/6 kV
Power factor	> 0.95
Through wiring	Single power cord entry
Operating temperature	-40...50°C
Power cord	20" of outdoor use rated flexible power cord
Packing box dimensions	31 1/2" * 7 7/8" * 9 27/32"

Project name				Type		Quantity	
Date		Note					
LC2029.864-US-T5-700-740-__-__-__							

Light distribution	Rated input power	Color temperature	Control	Product colors
[T5] Type V - 117°	[700] 135 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM3]  Anthracite gray
	[500] 97 W	[827] 2700 K CRI 80	[0-10V] 0-10V	[HM4]  Light gray
	[350] 68 W	[830] 3000 K CRI 80		[CC]  Custom color (Please specify RAL code)
[840] 4000 K CRI 80				
Extras				
Luminaire body options				
[DPC] Double powder coating				